

Pneum. contact metal OD 6 male



| Part number | 09 14 000 6356 |
|--------------------|-------------------------------------|
| Specification | Pneum. contact metal OD 6 male |
| HARTING eCatalogue | https://b2b.harting.com/09140006356 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Contacts |
|----------------------------|--|
| Type of contact | Pneumatic contact |
| Description of the contact | Without shut-off Straight |
| Features | The Han® Pneumatic contacts without shut-off are suitable for the use inside a vacuum. (Limit: 100 mbar = 100 hPa ≈ approx 90% vacuum) |

Version

| Gender | Male |
|-----------------------|-----------------|
| Manufacturing process | Turned contacts |

Technical characteristics

| Limiting temperature | [-20] [+85 °C] Tube outer diameter |
|----------------------|------------------------------------|
| Operating pressure | ≤10 bar |
| Tube outer diameter | 6 mm |

Material properties

| Material (contacts) | Brass |
|-----------------------------|--|
| Material (seal) | NBR |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |



Material properties

| REACH ANNEX XIV substances | No |
|----------------------------|--------------------------------------|
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | b51e5b97-eeb5-438b-8538-f1771d43c17d |

Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
|----------|--|
| CE | 0 |

Commercial data

| Packaging size | 10 |
|--------------------------------|--|
| Net weight | 13.9 g |
| Country of origin | Germany |
| European customs tariff number | 39269097 |
| eCl@ss | 27440204 Contact for industrial connectors |