


# Front panel valve SV-5-M5-B

Part number: 11914

FESTO



## Data sheet

| Feature                             | Value  |
|-------------------------------------|--|
| Valve function                      | 5/2, monostable  |
| Actuation type                      | Manual   |
| Standard nominal flow rate          | 95 l/min   |
| Operating pressure                  | 0 bar ... 8 bar  |
| Design                              | Poppet valve with return spring                                    |
| Reset method                        | Mechanical spring  |
| Nominal width                       | 2.3 mm   |
| Type code                           | SV   |
| Sealing principle                   | Soft   |
| Mounting position                   | Any  |
| Type of control                     | Direct   |
| Symbol                              | 00991339   |
| Lap                                 | Overlap  |
| Explosion prevention and protection | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Operating medium                    | Compressed air as per ISO 8573-1:2010 [-:~:]                       |
| Ambient temperature                 | -10 °C ... 60 °C   |
| Actuating force                     | 17 N   |
| Product weight                      | 53 g   |
| Type of mounting                    | Front panel mounting<br>With through-hole                          |
| Pneumatic connection 1              | M5   |
| Seals material                      | NBR  |
| Housing material                    | Polymer<br>Brass   |