

# Product data sheet

Specifications



## 15A 250V 1 Gang Switched Socket

KB15\_15

### Main

Range	Vivace
Product or component type	Switched socket
Device short name	KB15
Device presentation	Complete product

### Complementary

Outlet poles configuration	2P + E
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	15 A at 250 V AC, resistive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	N Earth L
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm <sup>2</sup>
Width	87 mm
Height	87 mm

### Environment

Standards	MS 589
-----------	--------

BS 1362-2  
SS 145

---

**Ambient air temperature for operation** -5...40 °C

---

**Relative humidity** 0...95 %

---

**Environmental characteristic** Indoor use

---

## Packing Units

---

**Package 1 Weight** 87.540 g

---

**Package 1 Height** 1.000 mm

---

**Package 1 Width** 1.000 mm

---

**Package 1 Length** 1.000 mm

---

## Offer Sustainability

---

**Sustainable offer status** Green Premium product

---

**REACH Regulation** [REACH Declaration](#)

---

**REACH free of SVHC** Yes

---

**EU RoHS Directive** Compliant  
[EU RoHS Declaration](#)

---

**Toxic heavy metal free** Yes

---

**Mercury free** Yes

---

**RoHS exemption information** [Yes](#)

---

**China RoHS Regulation** [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

---

**Environmental Disclosure** [Product Environmental Profile](#)

---

## Contractual warranty

---

**Warranty** 18 months

---