

PRODUCT-DETAILS

A75-30-00 220-230V 50Hz / 230-240V 60Hz A75-30-00 220-230V 50Hz / 230-240V 60Hz Contactor



General Information

Extended Product Type	A75-30-00 220-230V 50Hz / 230-240V 60Hz
Product ID	1SBL411001R8000
EAN	3471522092809
Catalog Description	A75-30-00 220-230V 50Hz / 230-240V 60Hz Contactor
Long Description	A75 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC / 1000 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SBL391001R8000

Popular Downloads

Data Sheet, Technical
Information

1SBC100122C0202_Ch02

Instructions and Manuals

FPTC407700P0003

Dimensions

Product Net Width	70 mm
Product Net Depth / Length	108 mm
Product Net Height	110 mm
Product Net Weight	1.16 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Standards	Devices complying with international standards IEC 947-1 / 947-4-1, and European standards EN 60 947-1 / 60 947-4-1. Electromagnetic compatibility (EMC) acc. to amendment A11 to IEC 947-1, EN 60 947-1 and amendment 2 to IEC 947-4-1
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Control Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 125 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 125 A (690 V) 55 °C 105 A (690 V) 70 °C 85 A
Rated Operational Current AC-3 (I_e)	(415 V) 55 °C 72 A (440 V) 55 °C 70 A (500 V) 55 °C 65 A (690 V) 55 °C 46 A (1000 V) 55 °C 28 A (380 / 400 V) 55 °C 75 A (220 / 230 / 240 V) 55 °C 75
Rated Operational Power AC-3 (P_e)	(415 V) 40 kW (440 V) 40 kW (500 V) 45 kW (690 V) 40 kW (1000 V) 37 kW (380 / 400 V) 37 kW (220 / 230 / 240 V) 22 kW
Rated Operational Power AC-6b (P_e)	(230 / 240 V) 40 °C, 50 / 60 Hz 28 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 28 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 24.5 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 48 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 41 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 48 kvar (440 V) 40 °C, 50 / 60 Hz 52 kvar (440 V) 55 °C, 50 / 60 Hz 52 kvar (440 V) 70 °C, 50 / 60 Hz 45 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 60 kvar

	(500 / 550 V) 55 °C, 50 / 60 Hz 60 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 51 kvar (690 V) 40 °C, 50 / 60 Hz 82 kvar (690 V) 55 °C, 50 / 60 Hz 82 kvar (690 V) 70 °C, 50 / 60 Hz 70 kvar
Rated Breaking Capacity AC-3	8 x I _e AC-3
Rated Making Capacity AC-3	10 x I _e AC-3
Short-Circuit Protective Devices	gG Type Fuses 160 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 650 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 135 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 370 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 1300 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 630 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 600 cycles per hour
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V
Coil Consumption	Average Holding Value 50 / 60 Hz 18 V·A Average Pull-in Value 50 Hz 190 V·A Average Pull-in Value 60 Hz 180 V·A
Operate Time	Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NO Contact Closing 8 ... 27 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH75-25 (75 x 25 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M6 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Cable End 6 ... 16 mm ² Rigid Cable 6 ... 25 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M 6 (+,-) pozidriv 2 screws with 1x (13 x 10 mm) connector
Terminal Type	Screw Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 105 A
Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 25 hp (220 ... 240 V AC) Three Phase 30 hp

(440 ... 480 V AC) Three Phase 60 hp
 (550 ... 600 V AC) Three Phase 75 hp

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 55 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 55 °C Close to Contactor without Thermal O/L Relay (Uc) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations

BV Certificate	BV_2634H07559E0
CB Certificate	CB_CN45324
CCC Certificate	CCC_2018010304129267 CCC_2008010309289461
CQC Certificate	CQC2018010304129267 CQC2008010309289461
Declaration of Conformity - CCC	2020980304001622 2020980304001226
Declaration of Conformity - CE	1SBD250801U1000
Declaration of Conformity - UKCA	1SBD250818U1000
DNV Certificate	DNV-GL_TAE00000TX
DNV GL Certificate	DNV-GL_TAE00000TX
EAC Certificate	EAC_RU C-FR ME77 B03599
LR Certificate	LRS_9830011E4
RINA Certificate	RINA_ELE172319XG001
RMRS Certificate	RMRS_0507015250
UL Certificate	UL-US-L312527-1101-21215991-6 UL-CA-2139468-4
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	140 mm
Package Level 1 Depth / Length	146 mm
Package Level 1 Height	96 mm
Package Level 1 Gross	1.16 kg

Weight

Package Level 1 EAN	3471522092809
Package Level 2 Units	box 20 piece
Package Level 2 Width	503 mm
Package Level 2 Depth / Length	153 mm
Package Level 2 Height	307 mm
Package Level 2 Gross Weight	23.2 kg
Package Level 3 Units	160 piece

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4756 >> Capacitor magnet contactor
E-Number (Finland)	3709224

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

