

PRODUCT-DETAILS

CR-U230AC2

CR-U230AC2 Pluggable interface relay 2c/o, A1-A2=230VAC, 250V/10A



General Information

| | |
|-----------------------|---|
| Extended Product Type | CR-U230AC2 |
| Product ID | 1SVR405621R3000 |
| EAN | 4013614498411 |
| Catalog Description | CR-U230AC2 Pluggable interface relay 2c/o, A1-A2=230VAC, 250V/10A |
| Long Description | The CR-U230AC2 pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 230 V AC rated control supply voltage and has 2 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated orange test button for manual actuation and locking of the output contacts. Standard sockets, pluggable function modules, holder and marker are available as accessories. |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|-----------------------------------|--------------------|
| Data Sheet, Technical Information | 2CDC110004C0210_05 |
| Instructions and Manuals | 1SVC405600M9000 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 35 mm |
| Product Net Height | 54.4 mm |
| Product Net Depth / Length | 35 mm |
| Product Net Weight | 0.083 kg |

Technical

| | |
|--|--|
| Function | Pluggable universal interface relay CR-U |
| Sub-Function | Relay w/o built in LED |
| Output | 2 c/o (SPDT) contacts |
| Output Signal | 250 V / 10 A |
| Rated Control Supply Voltage (U _s) | 230 V AC |
| Terminal Type | Pin |

Environmental

| | |
|--|--|
| Ambient Air Temperature | Operation -40 ... +55 °C Storage -40 ... +85 °C |
| Maximum Operating Altitude Permissible | Without Derating 2000 m |
| RoHS Status | Following EU Directive 2011/65/EU |

Technical UL/CSA

| | |
|----------------------------------|----------|
| Maximum Operating Voltage UL/CSA | 300 V AC |
| Ampere Rating UL/CSA | 5 A |
| Pilot Duty UL/CSA | B300 |

Certificates and Declarations (Document Number)

| | |
|---------------------------------|-----------------------------|
| CCC Certificate | CCC_2017010303949759 |
| CQC Certificate | CQC2017010303949759 |
| CSA Certificate | CSA_1587291 |
| Declaration of Conformity - CCC | 2020980303000199 |
| Declaration of Conformity - CE | 1SVD982021-0003 |
| EAC Certificate | EAC_RU_C-DE.ME77.B.00446-19 |
| Environmental Information | 1SAA981009-2401 |
| Instructions and Manuals | 1SVC405600M9000 |
| LR Certificate | LR_05_20002_E5 |
| RMRS Certificate | RMRS_1740019250 |
| RoHS Information | 1SVD982021-0003 |
| UR Certificate | UR_E244330 |
| VDE Certificate | VDE_40019116 |

Container Information

| | |
|-------------------------|--------------|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Width | 182 mm |
| Package Level 1 Height | 76 mm |
| Package Level 1 Depth / | 77 mm |

| | |
|------------------------------|---------------|
| Length | |
| Package Level 1 Gross Weight | 0.87 kg |
| Package Level 1 EAN | 4013614374074 |

Classifications

| | | |
|----------------------------|----------------------------|---|
| Object Classification Code | | K |
| ETIM 4 | EC001437 - Switching relay | |
| ETIM 5 | EC001437 - Switching relay | |
| ETIM 6 | EC001437 - Switching relay | |
| ETIM 7 | EC001437 - Switching relay | |
| eClass | V11.0 : 27371601 | |
| UNSPSC | 39122331 | |
| E-Number (Finland) | 2712795 | |
| E-Number (Sweden) | 4005415 | |

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

