

General Information

| | |
|------------------------|---|
| Extended Product Type: | CP-C 24/10.0 |
| Product ID: | 1SVR427025R0000 |
| EAN: | 4013614368684 |
| Catalog Description: | CP-C 24/10.0 Power supply In:110-240VAC/100-350VDC Out:DC 24V/10A |
| Long Description: | The CP-C 24/10.0 is a power supply from the CP-C range. The primary switch mode power supply offers a wide range input of 85-264 V AC and 100-350 V DC, rated input voltage is 110-240 V AC. The rated output power is 240 W, rated output current is 10 A at an output voltage of 24 V DC. The output voltage is adjustable within a range of 22 to 28 V DC. The power supply provides a U/I output characteristic with a power reserve of up to 20 % and allows parallel operation to increase capacity and to enable redundancy. Further features are: pluggable connecting terminals and power factor correction acc. to EN 61000-3-2. Messaging module, redundancy unit and control module are available as accessories. |

Categories

Products » Low Voltage Products and Systems » Control Products » Power Supplies
 Parts & Services » Drives » Medium Voltage AC Drives » Special Purpose Drives » ACS5000 water cooled

Ordering

| | |
|-------------------------|---------------|
| EAN: | 4013614368684 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85044090 |

Dimensions

| | |
|---------------------|----------|
| Product Net Width: | 93.5 mm |
| Product Net Height: | 130 mm |
| Product Net Depth: | 135.5 mm |
| Product Net Weight: | 1.368 kg |

Container Information

| | |
|-------------------------------|----------|
| Package Level 1 Width: | 142 mm |
| Package Level 1 Length: | 135 mm |
| Package Level 1 Height: | 112 mm |
| Package Level 1 Gross Weight: | 1.494 kg |
| Package Level 1 Units: | 1 piece |

Technical

| | |
|-------------------------------------|-------------------------------------|
| Function: | Switch mode power supply |
| Number of Phases: | 1 |
| Input Voltage (U _{in}): | 85 ... 264 V AC 110 ... 350 V DC |
| Output Voltage (U _{out}): | 24 V DC |
| Output Current: | 10 A |
| Output Power: | 240 W |

Environmental

| | |
|--------------|---|
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|--------------|---|

Certificates and Declarations (Document Number)

| | |
|---------------------------------|-----------------------------------|
| CB Certificate: | CB_DK-35488-UL |
| cUL Certificate: | cUL508_E174460 cUL1604_E215666 |
| cUR Certificate: | cUR60950_E196145 |
| Declaration of Conformity - CE: | 1SAD938503-0147 |
| EAC Certificate: | EAC_RU_C-DE.ME77.B.01651 |
| GOST Certificate: | GOST_POCC_CN.AB76.B00924 |
| RoHS Information: | 1SAA981008-4404 |
| UL Certificate: | UL508_E174460 UL1604_E215666 |
| UR Certificate: | UR60950_E196145 |

Classifications

| | |
|---------|--------------|
| eClass: | 7.0 27049002 |
|---------|--------------|