

[Home](#) > [Products](#) > [By Type](#) > [Relays](#) > [Product Feature Selector](#) > Product Details

## 2122D4YD Product Details



**2122D4YD**  
(1423154-1)

TE Internal Number: 1423154-1

**Active**

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- 2100 Miniature Timing Series
- Input Voltage = 125 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 120 VAC
- Mounting Options = Chassis Mount

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• Termination Type = 8-Pin Octal Style Plug</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• Input Voltage (VDC) = 125</li> <li>• Contact Rating = 10A @ 120 VAC</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Series</a> = 2100 Miniature Timing</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• Mounting Options = Chassis Mount</li> <li>• Mode of Operation = Off-Delay</li> <li>• Delay Time = 0.375 seconds to 3 seconds</li> <li>• Type of Control = Knob</li> <li>• Repeatability, Max. = ± 5% @ 25°C, ± 7% @ 85°C, ± 8% @ 55°C</li> <li>• Approved Standards = CE Approved</li> <li>• Approx. Dimensions (L x W x H) (mm [in]) = 63.50 x 38.60 x 123.90 [2.501 x 1.520 x 4.881]</li> </ul>	<p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Contact Arrangement</a> = 2 Form C, DPDT, 2 C/O</li> <li>• Multiple Timing Ranges = Without</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not suitable for lead free processing</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• Temperature Range (?C) = -55 - +85</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Agastat</li> </ul>

Corporate Information	Quick Links	Customer Support
<a href="#">Who We Are</a>	<a href="#">Check Distributor Inventory</a>	<a href="#">Email or Chat with Us</a>
<a href="#">Investors</a>	<a href="#">Cross Reference</a>	<a href="#">Find a Phone Number</a>
<a href="#">News Room</a>	<a href="#">Find Documents &amp; Drawings</a>	<a href="#">Search Knowledge Base</a>
<a href="#">Supplier Portal</a>	<a href="#">Product Compliance Support Center</a>	<a href="#">Manage Your Account</a>
<a href="#">Careers</a>	<a href="#">Site Map</a>	