


FLEXCON PRO

For heating and chilled water (cooling) installations.

- Replaceable bladder.
- Red (RAL 3002) epoxy powder coating.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- Max. operating pressure: 6.0 bar.
- Max. temperature on diaphragm (EN 13831/8): 70 °C.
- Max. temperature at (heating) outlet: 120 °C.
- In accordance with Pressure Equipment Directive 97/23/EC.
- Material quality: ASTM/ISO: A181 class 60 / S235JRG2.

Flexcon PRO								
Type	Capacity [l]	Pre-charge [bar]	Dimensions		Syst. conn. (M)	Weight [kg]		Order Code
			Ø [mm]	H. [mm]				
Flexcon PRO 200	200	2.5	550	1150	1"	47	1	25420
Flexcon PRO 250	250	2.5	550	1400	1"	55	1	25425
Flexcon PRO 300	300	2.5	550	1650	1"	63	1	25430
Flexcon PRO 370	370	2.5	650	1350	1"	74	1	25431
Flexcon PRO 430	430	2.5	750	1170	1"	87	1	25443
Flexcon PRO 540	540	2.5	750	1420	1"	108	1	25454
Flexcon PRO 650	650	2.5	750	1670	1"	125	1	25465
Flexcon PRO 770	770	2.5	750	1950	1"	153	1	25477
Flexcon PRO 870	870	2.5	750	2200	1"	172	1	25487
Flexcon PRO 1000	1000	2.5	750	2450	1"	180	1	25500

