



Motor fuse-link, medium voltage, 160 A, AC 3.6 kV, 50 kA, DIN 43625 3", 76 x 192 mm, back-up, DIN, with striker

**Part no.** 3.6KV 160Amp 3" 'J' Motorstart Fuse  
**Catalog No.** 3.6WFOSJ160

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Motor fuse-link
Field of application			medium voltage
Rated current	I	A	160
Rated voltage			AC 3.6 kV
Construction size			DIN 43625 3"
Size			76 x 192 mm
Utilization category			back-up
Status indicator			with striker
Breaking Capacity		kA	50
usable for size/applications			motor protection
Standard/Approval			DIN
Shape			cylindrical
Standards/Regulations			DIN 43625 VDE 0670-4 IEC 60282-1

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Safety fuse systems (unspecified) (ecl@ss10.0.1-27-14-21-90 [BAB265011])			
Rated current		A	160
Rated voltage		kV	3.6
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	0.05
Utilization category			Other
Application			Motor protection
Length		mm	192
Diameter		mm	76
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			DIN
Release characteristic			Other
Installation technique			Air