



PURGE/PRESSURIZATION SYSTEM

SERIES 3000/MODEL 3004

DATA SHEETS



Class I ($\leq 250 \text{ ft}^3$) and Zone 2 ($\leq 7.08 \text{ m}^3$)

Description

Model 3004 is a Rapid Exchange® purging system that operates on a supply of compressed instrument air or inert gas. It regulates and monitors pressure within sealed protected enclosure(s), in order to remove and prevent flammable gas or vapor accumulations. The Model 3004 consists of three major components: (1) a pneumatic manifold assembly, (2) a differential enclosure pressure indicator and (3) a stainless steel face plate with mounting flange, or a Lexan® system start up instruction nameplate. Model 3003 is offered in three distinct variations, identified as "VM" (Vertical Mount), "HM" (Horizontal Mount), both available in WPS & WPSA styles, and "CK" (Component Kit) mounting configurations. The VM configuration features a filter regulator and face plate with a flange for mounting to a vertical surface. The HM configuration features a regulator and face plate with a flange for mounting on a horizontal surface. Finally, the CK configuration is a kit of parts including the pneumatic manifold assembly, the enclosure pressure indicator and a start-up instruction nameplate. The VM and HM configurations are intended for flange or frame mounting to a solid surface on or near the protected enclosure(s), while the CK configuration is intended for frame mounting through cutouts in a panel on or near the enclosure(s). With the addition of a Model GCK gauge conversion kit, all configurations can be mounted through the surface of a protected enclosure. The CK configuration provides a seal that withstands type 4 hosedown testing. Model 3004 accomplishes the required volume exchanges and maintains a safe pressure. Pepperl+Fuchs Model EPV-3 enclosure protection vent is required for proper operation. This process reduces the hazardous (classified) area rating within protected enclosure(s), in accordance with the NEC - NFPA 70, NFPA 496, ISA 12.4 and IEC 600 79-15 EN 50021.

Operation

In accordance with system instructions, start-up requires air supply to be engaged and enclosure power to be deenergized. The enclosure protection vent must be tested and enclosure(s) must be sealed. After transferring the valve key, locked into the pneumatic manifold's Rapid Exchange control valve stem, the enclosure pressure control valve is used to set a safe reading on the enclosure pressure indicator. When safe pressure is stable, the valve key is transferred and locked into the Rapid Exchange control valve stem and the Rapid Exchange control valve is then fully engaged. Upon completion of the Rapid Exchange cycle, (five minutes minimum) the Rapid Exchange control valve is disengaged to return to a safe enclosure pressure. Power can then be energized to the protected enclosure(s). Loss of safe pressure requires immediate attention, unless power to the protected enclosure(s) is deenergized. WPS and WPSA style systems include an explosion proof differential pressure switch with form "C" contacts for audible or visual alarm systems.

Rapid Exchange® is a Registered Trademark of Pepperl+Fuchs, Inc.

Lexan® is a registered trademark of the General Electric Company

Model 3004



Model 3004-LPS-CI-YZ-VML Vertical Mount Configuration



Model 3004-WPS-CI-YZ-HMT Horizontal Mount Configuration



Model 3004-LPS-CI-YZ-CK Component Kit Configuration




Standard Model Applications

Model Number:	3004	Model Number:	3004
Designation:	Type Y System RapidExchange® Purging	Designation:	Type Z and Ex [nP] System Rapid Exchange® Purging
Enclosure Volume:	250 ft ³ (7.08 m ³) max.	Enclosure Volume:	250 ft ³ (7.08 m ³) max.
LPS Style		LPS Style	
UL & FM Certified:	Cl. I, Div. 1, Group A-D	UL & FM Certified:	Cl. I, Div. 2, Group A-D
Rating Reduction:	Div. 1 to Div. 2	ATEX 'nP' Certified:	Zone 2, Group IIC
WPS Style		WPS Style	
UL & FM Certified:	Cl. I, Div. 1, Group C-D	Rating Reduction:	Div. 2 to Nonhazardous Zone 2 to Nonhazardous
Rating Reduction:	Div. 1 to Div. 2	WPSA Style	
WPSA Style		UL & FM Certified:	Cl. I, Div. 2, Group C-D
UL & FM Certified:	Cl. I, Div. 1, Group A-D	Rating Reduction:	Div.2to Nonhazardous
Rating Reduction:	Div. 1 to Div. 2	WPSA Style	
		UL & FM Certified:	Cl. I, Div. 2, Group A-D
		ATEX 'nP' Certified:	Zone 2, Group IIB+H ₂
		Rating Reduction:	Div.2to Nonhazardous Zone 2 to Nonhazardous
Ex II 3G EEx [nP] II			

Model 3004 VM Configuration - The Vertical Mount System


LPS (Less Pressure Switch)



Important Notes

- 1) The VM configuration is supplied with a mounting flange for right angle-attachment to a vertical surface external to the protected enclosure.
- 2) The VM configuration can also be frame mounted external to the protected enclosure through a 5" (127 mm) W x 10.75" (273 mm) H cutout in a suitable mounting surface.
- 3) Model GCK gauge conversion kit is required to panel mount the VM configuration through a 5" (127 mm) W x 10.75" (273 mm) H cutout in the protected enclosure surface.
- 4) See page 60 for Model GCK kit description and conversion procedure.


WPS / WPSA (With Pressure Switch)



CONNECTION POINTS SHOWN ABOVE IN BOLD TEXT ON SYSTEM DIAGRAM

Model 3004 HM Configuration - The Horizontal Mount System


LPS (Less Pressure Switch)



Important Notes

- 1) The HM configuration is supplied with a mounting flange for right-angled attachment to a horizontal surface external to the protected enclosure.
- 2) The HM configuration can also be frame mounted external to the protected enclosure through a 10.25" (260 mm) W x 5.5" (140 mm) H cutout in a suitable mounting surface.
- 3) Model GCK gauge conversion kit is required to panel mount the HM configuration through a 10.25" (260 mm) W x 5.5" (140 mm) H cutout in the protected enclosure surface.
- 4) See page 60 for Model GCK kit description and conversion procedure.

WPS / WPSA (With Pressure Switch)




CONNECTION POINTS SHOWN ABOVE IN BOLD TEXT ON SYSTEM DIAGRAM

Model 3004 CK Configuration - The Component Kit System

Part #1
Enclosure Pressure Indicator



Front View




Rear View


Atmospheric Reference

Venturi Orifice

Part #2
Pneumatic Manifold Assembly



Front View



Rear View

Part #3
Rapid Exchange® Injection Pressure Indicator



Front View



Side View



Part #4
Start Up Instruction Nameplate


CONNECTION POINTS SHOWN ABOVE IN BOLD TEXT ON SYSTEM DIAGRAM

Important Notes

- 1) The CK Configuration is four discrete parts suitable for mounting through a set of cutouts in a vertical surface external to the protected enclosure.
- 2) A Model GCK gauge conversion kit is required to panel mount the CK configuration through a set of cutouts in the protected enclosure surface.
- 3) See page 60 for Model GCK kit description and conversion procedure.

CK Configuration System & Optional Remote Cube Filter Dimensions in Inches (mm)


Pneumatic Manifold




Side View

Front View

Model 3004 CK System Panel Cutout Pattern



Enclosure Pressure Gauge




Front View

Side View


Helpful Hint

Note: Two optional Enclosure Pressure Gauge positions are shown on the Model 3004 CK System Panel Cutout Pattern to the left. The optional positions center gauge to the right or bottom side of System Nameplate.
Cut only one 4.5" (114.3 mm) Ø hole in panel.

Side View
Model RCF-8




Model RCF-8 Panel Cutout Pattern



3000 SERIES


Type Y, Z & Ex [nP]

Model 3004 WPS VM Configuration & Flange Dimensions in Inches (mm)




VM Configuration Front View


LPS (Less Pressure Switch)



VM Configuration Side View




Vertical Mount Flange Front View




WPS/WPSA VM Configuration Front View

WPS/WPSA (With Pressure Switch)




WPS/WPSA VM Configuration Side View




WPS/WPSA Vertical Mount Flange Front View

Model 3004 HM Configuration & Flange Dimensions in Inches (mm)




LPS HM Configuration Front View


LPS (Less Pressure Switch)



LPS HM Configuration Side View




LPS Horizontal Mount Flange Front View




WPS/WPSA HM Configuration Front View

WPS/WPSA (With Pressure Switch)



WPS/WPSA HM Configuration Side View




WPS/WPSA Horizontal Mount Flange Front View

Typical Model 3004 System Installation Details


External to the Protected Enclosure

Flange Mount HM Configuration with Model SMK-1 Fastener Kit



Internal to the Protected Enclosure

Panel Mount CK Configuration with Model RCF-8 Remote Cube Filter & Model GCK Gauge Conversion Kit




3000 SERIES
Type Y, Z & Ex [nP]


Standard and Panel Mount Pneumatic Installation Diagram

Standard Pneumatic Installation Diagram

See panel mounting conversion procedure on page 60



Panel Mount Installation Diagram



VM Configuration Mounting Options



Model 3004-LPS-CI-YZ-VML
Flange Mounted to
Flat Vertical Surface with
Model SMK-1 Fastener Kit




Model 3004-LPS-CI-YZ-VML
Flange Mounted to
Vertical 2" Pipe Stand with
Model PMK-1 Fastener Kit



Model 3004-LPS-CI-YZ-VM
Frame or Panel* Mounted
Through Cutout in Suitable Surface
with Model SMK-6m Fastener Kit


HM Configuration Mounting Options



Model 3004-LPS-CI-YZ-HMT
Flange Mounted to
Flat Horizontal Surface with
Model SMK-1 Fastener Kit



Model 3004-LPS-CI-YZ-HMB
Flange Mounted to
Horizontal 2" Pipe Stand with
Model PMK-1 Fastener Kit



Model 3004-LPS-CI-YZ-HM
Frame or Panel* Mounted
Through Cutout in Suitable Surface
with Model SMK-6m Fastener Kit

CK Configuration Mounting Options



Front View



Rear View


Model 3004-LPS-CI-YZ-CK
Rear View of Frame or Panel* Mount
Through Cutout in Suitable Surface with supplied fasteners

* PANEL MOUNTED SYSTEMS REQUIRE A PEPPERL+FUCHS MODEL GCK FOR PROPER OPERATION - SEE PAGE 60

3000
SERIES

Type Y, Z & Ex [nP]

Model 3004 Panel Mount Conversion



1. Secure one Model GCK Conversion Kit, kit includes a PRB-4 & SC-2 Fitting & Enclosure Pressure Gauge gasket.
2. Remove venturi orifice and run tee from the high port of the gauge and discard.
3. Remove sintered vent from low port.
4. Reinstall sintered vent into high port.
5. Install Model SC-2 fitting into low port.
6. Install Gauge gasket between gauge & mounting surface.
7. Install Model PRB-4 fitting through enclosure surface (vent end out) and connect tubing (customer supplied) between SC-2 & PRB-4.

System Specifications

System Dimensions:	See page 6
Shipping Weight:	LPS-12 lb (5.4 kg) WPS-17 lb (7.7 kg)
Temp. Range:	-20 °F to +120 °F (-29 °C to +49 °C)
Supply Pressure Range:	80 - 120 psi (5.5 - 8.3 bar)
Capacity & Filtration:	8.5 oz @ 40 Micron
Supply Requirements:	clean air or inert gas
Safe Press. Setpoint:	0.25" (6.35 mm)
Safe Press. Flow Rate:	* 0.1 - 3.5 SCFH (2.8 - 99 l/hr)
Exchange Pressure:	* 3" - 5" (76.2mm - 127 mm)
Exchange Flow Rate:	** 30 SCFM /1800 SCFH (850 l/m / 50976 l/hr)
Exchange Time:	
4 Volume Exchange Rate:	1 min / 7.5 ft ³ (212.4 l/m)
5 Volume Exchange Rate:	1 min / 6.0 ft ³ (169.9 l/m)
System Supply Port:	1/2" FPT
Enclosure Supply Port:	1/2" FPT
Enclosure Reference Fitting:	1/4" Tube
Switch Setting (WPS & WPSA Only):	0.15" ± 0.02" (3.81 mm ± 0.51 mm)
Switch Conduit Port Size:	1/2" FPT
Switch Contact Ratings:	
WPS Style:	120 VAC @ 15 A
WPSA Style:	*** 120/220 VAC, 24 VDC @ 10 A; 125 VDC @ 50 mA
Switch (WPSA) Power Requirement:	24 / 120 / 240 VDC @ 3 / 4 / 11 watts


* Enclosure integrity determines actual flow rate
 ** With regulator set to 60 psi min. during exchange
 *** Supply voltages 24 VDC and 240 VAC available upon request.

Material Specifications

Regulator Body:	Zinc w/Enamel Finish
Regulator Handle & Bowl*:	Polycarbonate
Enclosure Pressure Gauge:	Alum. w / Enamel Finish
Rapid Exchange® Gauge:	Poly & Nickel Plated
Tube Fitting:	316 SS Forged Body
Tubing:	316 SS 1/4" .035 Welded
Fastener Hardware:	Alum. & Stainless Steel
System Face Plate:	316 14 Ga #3 Brush SS
System Mounting Flange:	316 SS Tumble Finish
Manifold Body:	Anodized Aluminum
Manifold Valves:	316 Stainless Steel
Mfr. ID Nameplate:	Silkscreen Lexan®
Enclosure Warning Nameplate:	Silk screened SS
EXP Pressure Switch Body:	Anodized Cast Aluminum

* Refers to filter bowl supplied with VM mounting configuration.

Model Number Designations



Model 3004 System Accessories (See accessories page for complete details)

CONNECTION FITTINGS	
NC-8	1/2" T x 1/2" P Ninety Connector
SC-8	1/2" T x 1/2" P Straight Connector
EFC-4	1/4" Flush Connector
EBC-4	1/4" Bulkhead Connector
EFC-8	1/2" Flush Connector
EBC-8	1/2" Bulkhead Connector
EPC-14	1 1/2" Pipe Connector

ADDITIONAL ITEMS	
SMK-1	System Mounting Kit - Flange
SMK-6m	System Mounting Kit - Frame/Panel

PMK-1	Pipe Mounting Kit
GCK	Gauge Conversion Kit
ILF-8	1/2" In-Line Filter Kit
RCF-8	1/2" Remote Cube Filter
EPSK-1	Explosion Proof Switch Kit (GRP C, D)
EPSK-1A	Explosion Proof Switch Kit (GRP A-D)
GPSK-1	General-purpose Switch Kit
RAH	Remote Alarm Horn
RAB-1	Div. 1 Remote Alarm Beacon
RAB-2	Div. 2 Remote Alarm Beacon

ENCLOSURE PROTECTION VENTS	
ONE VENT REQUIRED WITH EACH SYSTEM	
EPV-4-SA-00	Straight w/Spark Arrestor
EPV-4-SA-90	Rt Angle w/Spark Arrestor
WARNING NAMEPLATES	
EWN-1	Class I Enclosure Warning
ETW	Enclosure Temperature Warning
INSTALLATION & OPERATION MANUAL	
129-0216	Inst. & Operation Manual

ONE (1) ENCLOSURE WARNING NAMEPLATE & ONE (1) INSTALLATION & OPERATION MANUAL ARE PROVIDED WITH EACH SYSTEM

Pepperl+Fuchs supplies purge/pressurization systems custom built to your specifications. To ensure the integrity of your system, certain accessory items must be factory installed.

The Model Number and Accessories Guide identifies those parts that must be included on your purge/pressurization system order.

3000 Series – Model Number Designations and Accessories Guide

3000 SERIES

Type Y, Z & Ex [nP]

3000 - - - - -

