


---

PRODUCT-DETAILS

# 3GBP202410-ADG

## M3BP 200MLA 4



---

### General Information

Product ID	3GBP202410-ADG
ABB Type Designation	M3BP 200MLA 4
Catalog Description	M3BP 200MLA 4

---

### Additional Information

ABB Type Designation	M3BP 200MLA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6210/C3
Country of Origin	Finland (FI) China (CN) India (IN) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	30.00 kW	1480 r/min	32.10 A	0.840	93.20 %	193.00 N·m	7.40
D	--	50 Hz	400 V	30.00 kW	1480 r/min	55.30 A	0.840	93.20 %	193.00 N·m	7.40
D	--	50 Hz	415 V	30.00 kW	1482 r/min	53.80 A	0.830	93.40 %	193.00 N·m	7.90
D	--	60 Hz	440 V	30.00 kW	1781 r/min	50.10 A	0.840	93.50 %	160.00 N·m	7.70
D	--	60 Hz	460 V	30.00 kW	1783 r/min	48.30 A	0.830	93.80 %	160.00 N·m	8.40

Gross Weight	301 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.2 % Partial Load (75%) 94.0 % Partial Load (50%) 93.7 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.5 % Partial Load (75%) 93.9 % Partial Load (50%) 93.2 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 200MLA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	291 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
Replaced Product ID (OLD)	3GBP202031-ADG
Selling Unit of Measure	piece
Standards	IEC 60034-1
Stocked At (Warehouses)	Central Stock Europe
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

