

68820630

Knife-edge fuse with striker gG type NH S3 500Vac 630A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Link to the reference



https://apac.socomec.com/en/reference/ 68820630 Industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908
Commerce	
Effective date	1988-04-15
Country of origin	HU
Discount Policy	1CF30
Discount Policy Label	FUSE WITH STRIKER
Length of the product unit	0.076
Width of the product unit	0.1525
Depth of the product unit	0.075
Weight	0.881
ETIM - Electrical characteristics	
Voltage type	AC
Rated current [A]	630
Rated voltage AC [V]	500
ETIM - Technical features	
Fuse construction type according to IEC 60269	NH3
Logistics	
GTIN/EAN	3596031408719
Customs number	8536109090
Price unit	PC
Weight of the packing unit	0.881
Length of the packing unit	0.23
Width of the packing unit	0.16
Width of the packing unit Depth of the packing unit	0.16 0.09
Depth of the packing unit	
Depth of the packing unit Norms	0.09
Depth of the packing unit Norms Conformity to standards	0.09
Depth of the packing unit Norms Conformity to standards Technical Characteristics	0.09 IEC
Depth of the packing unit Norms Conformity to standards Technical Characteristics Fuse melting indicator	0.09 IEC with striker
Depth of the packing unit Norms Conformity to standards Technical Characteristics Fuse melting indicator Fuse size	0.09 IEC with striker S3
Depth of the packing unit Norms Conformity to standards Technical Characteristics Fuse melting indicator Fuse size Rated voltage	0.09 IEC with striker S3 500 VAC