

SIPLUS NET PN/PN COUPLER T1 RAIL -25 ... +55°C T1 with 70°C for 10 min with conformal coating based on 6ES7158-3AD01-0XA0 .
Coupling module for connecting of two PROFINET networks
Transmission via PROFI-safe redundant current infeed



Installation type/mounting	
Mounting	Mounting rail 7.5 mm and 15 mm
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	20 ms
Input current	
from supply voltage 1L+, max.	400 mA
Power loss	
Power loss, typ.	6 W
Interfaces	
Supports protocol for PROFINET IO	
<ul style="list-style-type: none"> automatic detection of transmission rate 	Yes
<ul style="list-style-type: none"> Transmission rate, max. 	100 Mbit/s

- Number of RJ45 ports 4; 2 for each side

Protocols

Supports protocol for PROFINET IO Yes

Protocols (Ethernet)

- SNMP Yes
- ping Yes
- ARP Yes

Isochronous mode

Isochronous operation (application synchronized up to terminal) No; For operation on isochronous bus

Interrupts/diagnostics/status information

Status indicator Yes

Alarms Yes

Diagnostics function Yes

Diagnostics indication LED

- Bus fault BF (red) Yes; for each side
- Group error SF (red) Yes; for each side
- Monitoring 24 V voltage supply ON (green) Yes; for each side
- Connection to network LINK (green) Yes; for each port

Potential separation

between supply voltage and electronics Yes; to power input 2

between Ethernet and electronics Yes

Permissible potential difference

between different circuits 500 V DC

Isolation

Isolation tested with 707 V DC (type test) and according to EN 50155 (routine test)

Standards, approvals, certificates

Railway application

- EN 50121-3-2 Yes; EMC for rail vehicles
- EN 50121-4 Yes; EMC for signal and telecommunications systems
- EN 50124-1 Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC
- EN 50125-1 Yes; Rail vehicles - see ambient conditions
- EN 50125-2 Yes; Stationary electrical equipment - see ambient conditions
- EN 50125-3 Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track)
- EN 50155 Yes; Rail vehicles - temperature class T1, horizontal mounting position, salt spray Class ST2
- EN 61373 Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B

- Fire protection acc. to EN 45545-2

Yes; Rail vehicles - verification on request

Ambient conditions

Ambient temperature during operation	
<ul style="list-style-type: none"> • min. • max. 	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C 60 °C; = Tmax; +70 °C for 10 min (T1 acc. to EN 50155)
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. • Ambient air temperature-barometric pressure-altitude 	2 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
<ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 • Protection against fouling acc. to EN 60664-3 • Electronic equipment on rolling stock acc. to EN 50155 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A 	<p>Yes; Class 2 for high availability</p> <p>Yes; Type 1 protection</p> <p>Yes; Class PC2 protective coating acc. to EN 50155:2017</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>

Dimensions

Width	120 mm; Minimized with good handling
Height	119.5 mm
Depth	75 mm; with mounting rail

Weights

Weight, approx.	283 g
-----------------	-------

Other

Note:	For use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A Online Support article 109736776
-------	---

last modified: 05/29/2019