



Fuse-link, LV, 6 A, AC 500 V, D2, gR, IEC, fast acting

Catalog No. 6D27Q

EL-Nummer (Norway) 1601279

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	6
Rated voltage			AC 500 V
Construction size			D2
Utilization category			gR
Breaking Capacity		kA	50
usable for size/applications			E27
Release characteristic	class		fast-acting
Standard/Approval			IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])			
Construction size			DII
Rated current		A	6
Rated voltage		V	500
Colour code			Green
Utilization category			gR (general purpose semiconductor protection)
Release characteristic			Fast (F)

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/89d39a2a-2145-4922-a1f3-087f5ab42c22.pdf
-------------------------	---