

SITOP PSU300S 24 V/20 A
 SITOP PSU300S 20 A Stabilized power supply input: 3 AC 400-500 V output: 24 V DC/20 A



Input	
Input	3-phase AC
Rated voltage value V_{in} rated	400 ... 500 V
Voltage range AC	340 ... 550 V
Wide-range input	Yes
Mains buffering at I_{out} rated, min.	6 ms; at $V_{in} = 400$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 400 V	1.2 A
• at rated input voltage 500 V	1 A
Switch-on current limiting (+25 °C), max.	36 A
I^2t , max.	0.9 A ² ·s
Built-in incoming fuse	none
Protection in the mains power input (IEC 898)	Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)

Output

Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	24 V
Total tolerance, static \pm	3 %
Static mains compensation, approx.	0.5 %
Static load balancing, approx.	1 %
Residual ripple peak-peak, max.	150 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Adjustment range	24 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; max. 480 W
Status display	Green LED for 24 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"
On/off behavior	No overshoot of V_{out} (soft start)
Startup delay, max.	1.5 s
Voltage rise, typ.	30 ms
Voltage increase time of the output voltage maximum	500 ms
Rated current value I_{out} rated	20 A
Current range	0 ... 20 A
• Note	24 A up to +45°C; +60 ... +70 °C: Derating 5%/K
Supplied active power typical	480 W
Short-term overload current	
• on short-circuiting during the start-up typical	35 A
• at short-circuit during operation typical	35 A
Duration of overloading capability for excess current	
• on short-circuiting during the start-up	100 ms
• at short-circuit during operation	100 ms
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at V_{out} rated, I_{out} rated, approx.	91 %
Power loss at V_{out} rated, I_{out} rated, approx.	47 W

Closed-loop control

Dynamic mains compensation (V_{in} rated ± 15 %), max.	3 %
Dynamic load smoothing (I_{out} : 50/100/50 %), $U_{out} \pm$ typ.	3 %
Load step setting time 50 to 100%, typ.	2 ms
Load step setting time 100 to 50%, typ.	2 ms
Dynamic load smoothing (I_{out} : 10/90/10 %), $U_{out} \pm$ typ.	3 %
Load step setting time 10 to 90%, typ.	2 ms
Load step setting time 90 to 10%, typ.	2 ms

Setting time maximum	10 ms
----------------------	-------

Protection and monitoring

Output overvoltage protection	protection against overvoltage in case of internal fault $V_{out} < 35\text{ V}$
Current limitation, typ.	25 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Enduring short circuit current RMS value <ul style="list-style-type: none"> • maximum 	7 A
Overcurrent overload capability in normal operation	overload capability 150 % I _{out} rated up to 5 s/min

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current <ul style="list-style-type: none"> • maximum • typical 	3.5 mA 1 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nAC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
FM approval	-
CB approval	Yes
Marine approval	ABS, DNV GL
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature <ul style="list-style-type: none"> • during operation — Note • during transport • during storage 	0 ... 70 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics

Connection technology	screw-type terminals
Connections	

<ul style="list-style-type: none"> • Supply input 	L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded
<ul style="list-style-type: none"> • Output 	+, -: 2 screw terminals each for 0.2 ... 4 mm ²
<ul style="list-style-type: none"> • Auxiliary 	13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ²
Width of the enclosure	90 mm
Height of the enclosure	145 mm
Depth of the enclosure	150 mm
Required spacing	
<ul style="list-style-type: none"> • top 	40 mm
<ul style="list-style-type: none"> • bottom 	40 mm
<ul style="list-style-type: none"> • left 	0 mm
<ul style="list-style-type: none"> • right 	0 mm
Weight, approx.	1.6 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Buffer module
Mechanical accessories	Device identification label 20 mm × 7 mm, pale turquoise 3RT1900-1SB20
MTBF at 40 °C	571 429 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)