



Electronics module for ET 200S, 8DI 24 V DC 15 mm width, 1 unit per packing unit

Figure similar

Supply voltage	
Rated value (DC)	24 V; From power module
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Number of outputs	0; no encoder supply
Power loss	
Power loss, typ.	1.2 W
Address area	
Address space per module	
• Address space per module, max.	1 byte
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes; 2-wire sensors connectable
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+15 to +30 V
Input current	
• for signal "1", typ.	5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	2 ms
— at "0" to "1", max.	4.5 ms
— at "1" to "0", min.	2 ms
— at "1" to "0", max.	4.5 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No

Diagnostics indication LED	
• Status indicator digital input (green)	Yes
Parameter	
Remark	3-byte parameter (not accessible for the user)
Potential separation	
Potential separation digital inputs	
• between the channels	No
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	35 g

last modified: 2/9/2021 