

Spare part SIMATIC DP, electronic module for ET 200L 16 DO, 24 V DC/0.5 A



Figure similar

General information	
Vendor identification (VendorID)	0016h
Usable terminal block	TB 16L
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	20 ms
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V; 1L+, 2L+, 3L+
Input current	
from supply voltage L+, max.	70 mA; L4+ / L5+
from load voltage L+ (without load), max.	50 mA; Per load group (L1+ or L2+ / L3+)
Power loss	
Power loss, typ.	5 W
Digital outputs	

Number of digital outputs	16
Short-circuit protection	Yes
• Response threshold, typ.	0.7 A
Limitation of inductive shutdown voltage to	Typ. (L1+ or L2+ / L3+) -55 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	41 Ω
• upper limit	28 000 Ω
Output voltage	
• Rated value (DC)	24 V
• for signal "1", min.	Ua - 3 V
Output current	
• for signal "1" permissible range, min.	1 mA
• for signal "1" permissible range, max.	0.5 A
• for signal "0" residual current, max.	1 mA
Output delay with resistive load	
• "0" to "1", max.	50 μ s
• "1" to "0", max.	200 μ s
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; only outputs of the same group
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	8 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 30 °C, max.	4 000 mA
— up to 40 °C, max.	3 000 mA
— up to 60 °C, max.	2 000 mA
all other mounting positions	
— up to 40 °C, max.	2 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interfaces	
PROFIBUS DP	
• Transmission rate, max.	1.5 Mbit/s
• SYNC capability	Yes

- Direct data exchange (slave-to-slave communication)

Yes; Transmitter (for digital outputs and hybrid modules ET 200L: not for L-SC or IM-SC)

Protocols

Bus protocol/transmission protocol PROFIBUS DP

Interrupts/diagnostics/status information

Alarms No

Diagnostics function Yes

Diagnostics indication LED

- Bus fault BF (red) Yes
- Status indicator digital output (green) Yes
- Monitoring 24 V voltage supply ON (green) Yes

Potential separation

between PROFIBUS DP and all other circuit components Yes

Potential separation digital outputs

- between the channels No
- between the channels and PROFIBUS DP Yes; Optocoupler

Isolation

Isolation tested with 500 V DC

Degree and class of protection

IP degree of protection IP20

Ambient conditions

Ambient temperature during operation

- horizontal installation, min. 0 °C
- horizontal installation, max. 60 °C; 40°C for other mountings

Air pressure acc. to IEC 60068-2-13

- permissible range, lower limit 795 hPa
- permissible range, upper limit 1 080 hPa

Relative humidity

- Operation, min. 5 %
- Operation, max. 95 %; RH class 2 in accordance with IEC 1131-2

Vibrations

- Operation, tested according to IEC 60068-2-6 Yes; IEC 68, Part 2-6; 10 to 57 Hz; (constant amplitude 0.075 mm); 57 to 150 Hz; (constant acceleration 1 g)

Shock testing

- tested according to IEC 60068-2-27 Yes; IEC 68, Part 2-27; half-sine, 15 g, 11 ms

Connection method

Design of electrical connection for the inputs and outputs Screw-type and spring-loaded terminals, permanent wiring; standard: 2-wire connection, optional: 3 and 4-wire connection

Dimensions

Width	145 mm
Height	60 mm
Depth	60.5 mm

Weights

Weight, approx.	130 g
-----------------	-------

last modified: 04/15/2019