

SIMATIC DP, 5 electronic modules for ET 200S, 4 DO High Feature 24 V DC/0.5 A, 15 mm width, Diagnostics short circuit, SF LED 5 units per packing unit



Figure similar

Supply voltage	
Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V; From power module
<ul style="list-style-type: none"> Reverse polarity protection 	Yes; polarity reversal can lead to the digital outputs being connected through
Input current	
from load voltage L+ (without load), max.	5 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.8 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Address space per module, max. 	1 byte
<ul style="list-style-type: none"> with packing 	4 bit
Digital outputs	

Number of digital outputs	4
Short-circuit protection	Yes
• Response threshold, typ.	0.7 to 1.5 A
Limitation of inductive shutdown voltage to	-55 to -60 V, L+()
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	3 400 Ω
Output voltage	
• for signal "1", min.	L+ (-1 V)
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	7 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	0.3 mA
Output delay with resistive load	
• "0" to "1", max.	100 μs
• "1" to "0", max.	300 μs
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; per module
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per module, max.	2 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnostic messages	
• Short-circuit	Yes; Module-wise
Diagnostics indication LED	
• Group error SF (red)	Yes

- Status indicator digital output (green) Yes; Per channel

Parameter

Remark 3 byte

Potential separation

Potential separation digital outputs

- between the channels No
- between the channels and backplane bus Yes

Isolation

Isolation tested with 500 V DC

Dimensions

Width 15 mm

Height 81 mm

Depth 52 mm

Weights

Weight, approx. 40 g

last modified: 04/16/2019