

SIMATIC S7-1500, Digital output module DQ 16x 230 V AC/2A ST;  
Relay 16 channels in groups of 2; 4 A per group; switching cycle  
counter for integrated relay, diagnostics; substitute value: front  
connector (screw terminals or push-in) order separately



General information	
Product type designation	DQ 16x 230 V AC/2 A ST (relay)
HW functional status	From FS02
Firmware version	V1.1.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V13 SP1 / -
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No

• Oversampling	No
• MSO	Yes
• Integrated operating cycle counter	Yes; FW V1.1.0 or higher

#### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

#### Input current

Current consumption, max.	185 mA
---------------------------	--------

#### Output voltage

Rated value (AC)	230 V; 24 V DC to 120 V DC / 24 V AC to 230 V AC
------------------	--

#### Power

Power available from the backplane bus	0.8 W
--	-------

#### Power loss

Power loss, typ.	5 W
------------------	-----

#### Digital outputs

Type of digital output	Relays
Number of digital outputs	16
Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	No
Controlling a digital input	Yes
Size of motor starters according to NEMA, max.	5

#### Switching capacity of the outputs

• on lamp load, max.	50 W (230 V AC), 5 W (24 V DC)
----------------------	--------------------------------

#### Output current

• for signal "1" rated value	2 A
• for signal "1" permissible range, min.	10 mA; 10 V
• for signal "1" permissible range, max.	2 A; thermal continuous current
• for signal "0" residual current, max.	0 A

#### Parallel switching of two outputs

• for logic links	Yes
• for uprating	No
• for redundant control of a load	Yes

#### Switching frequency

• with resistive load, max.	1 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz

Total current of the outputs	
• Current per channel, max.	2 A; see additional description in the manual
• Current per group, max.	4 A; see additional description in the manual
• Current per module, max.	32 A; see additional description in the manual
Relay outputs	
• Number of relay outputs	16
• Rated supply voltage of relay coil L+ (DC)	24 V
• Current consumption of relays (coil current of all relays), typ.	185 mA
• external protection for relay outputs	Miniature circuit breaker B10 / B16
• Contact connection (internal)	No
• Number of operating cycles, max.	see additional description in the manual
• Relay approved acc. to UL 508	No
Switching capacity of contacts	
— with inductive load, max.	2 A; see additional description in the manual
— with resistive load, max.	2 A; see additional description in the manual
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	No
• Short-circuit	No
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	No
• for module diagnostics	Yes; red LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels, in groups of	2
• between the channels and backplane bus	Yes

- Between the channels and load voltage L+

Yes

### Permissible potential difference

between different circuits

250 V AC between the channels and the supply voltage L+; 250 V AC between the channels and the backplane bus; 500 V AC between the channels

### Isolation

Isolation tested with

Between channels: 3 100 V DC; between channels backplane bus: 3 100 V DC; between L+ and backplane bus: 707 V DC (type test)

### Standards, approvals, certificates

Suitable for safety functions

No

### Ambient conditions

Ambient temperature during operation

- horizontal installation, min. -25 °C; From FS02
- horizontal installation, max. 60 °C
- vertical installation, min. -25 °C; From FS02
- vertical installation, max. 40 °C

### Dimensions

Width	35 mm
Height	147 mm
Depth	129 mm

### Weights

Weight, approx. 350 g

**last modified:** 10/05/2020