

### Product type designation

### CP 343-1 Lean

Communications processor CP 343-1 Lean for connection of SIMATIC S7-300 to Industrial Ethernet via TCP/IP and UDP, Multicast, SEND/RECEIVE with and without RFC1006, Fetch/ Write, S7 communication (server), PROFINET IO device integrated 2-port switch ERTEC 200, Module replacement without PG, SNMP diagnostics, initialization via LAN, 2x RJ45 connection for LAN with 10/100 Mbit/s



### Transmission rate

#### Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

### Interfaces

#### Number of interfaces / acc. to Industrial Ethernet

2

#### Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

2

1

#### Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet
- of Industrial Ethernet interface
- for power supply

RJ45 port

RJ45 port

2-pole plugable terminal block

### Supply voltage, current consumption, power loss

#### Type of voltage / of the supply voltage

DC

#### Supply voltage / 1 / from backplane bus

5 V

#### Supply voltage

24 V

#### Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
<ul style="list-style-type: none"> <li>• from backplane bus / at DC / at 5 V / typical</li> </ul>	0.2 A
<ul style="list-style-type: none"> <li>• from external supply voltage / at DC / at 24 V / typical</li> </ul>	0.16 A
<ul style="list-style-type: none"> <li>• from external supply voltage / at DC / at 24 V / maximum</li> </ul>	0.2 A
Power loss [W]	5.8 W

### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• for vertical installation / during operation</li> </ul>	0 ... 40 °C
<ul style="list-style-type: none"> <li>• for horizontally arranged busbars / during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP20

### Design, dimensions and weight

Module format	Compact module S7-300 single width
Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.22 kg
Mounting type	
<ul style="list-style-type: none"> <li>• S7-300 rail mounting</li> </ul>	Yes

### Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	8
Amount of data	
<ul style="list-style-type: none"> <li>• as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>• as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>• as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	2 Kibyte

Number of Multicast stations	8
<b>Performance data / S7 communication</b>	
Number of possible connections / for S7 communication	
• maximum	4
Service	
• of SIMATIC communication / as server	Yes
<b>Performance data / multi-protocol mode</b>	
Number of active connections / with multi-protocol mode	12
<b>Performance data / PROFINET communication / as PN IO-Controller</b>	
Product function / PROFINET IO controller	No
<b>Performance data / PROFINET communication / as PN IO-Device</b>	
Product function / PROFINET IO device	Yes
Amount of data	
• as user data for input variables / as PROFINET IO device / maximum	512 byte
• as user data for input variables / as PROFINET IO device / maximum	512 byte
• as user data for input variables / for each sub-module as PROFINET IO device	240 byte
• as user data for input variables / for each sub-module as PROFINET IO device	240 byte
• as user data for the consistency area for each sub-module	240 byte
Number of submodules / per PROFINET IO-Device	32
<b>Performance data / telecontrol</b>	
Protocol / is supported	
• TCP/IP	Yes
<b>Product functions / management, configuration</b>	
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	Yes
Configuration software	
• required	STEP 7 V5.4 or higher / STEP 7 Professional V11 (TIA Portal) or higher
Identification & maintenance function	
• I&M0 - device-specific information	Yes

- I&M1 – higher-level designation/location designation

Yes

### Product functions / Diagnosis

Product function / Web-based diagnostics

Yes

### Product functions / switch

Product feature / Switch

Yes

Product function

- switch-managed
- with IRT / PROFINET IO switch
- Configuration with STEP 7

No

No

Yes

### Product functions / Redundancy

Product function

- Ring redundancy
- Redundancy manager

Yes

No

Protocol / is supported / Media Redundancy Protocol (MRP)

Yes

### Product functions / Security

Product function

- password protection for Web applications
- ACL - IP-based
- ACL - IP-based for PLC/routing
- switch-off of non-required services
- Blocking of communication via physical ports
- log file for unauthorized access

No

Yes

No

Yes

Yes

No

### Product functions / Time

Product function / SICLOCK support

Yes

Product function / pass on time synchronization

Yes

Protocol / is supported

- NTP

Yes

### Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

### Security information

---

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

07/10/2019