

product type designation

product description

ITP Standard Cable GP for Industrial Ethernet

Industrial twisted pair cable (4-core), sold by the meter, unassembled

ITP Standard Cable for Industrial Ethernet J-02YSCY 2x2X0.64/1.5 PIMF F, installation cable 2x2-core for on-site assembly of connector, non-assembled, Sold by the meter Minimum order quantity: 20 m Delivery unit: max. 1000 m



suitability for use

Used in the construction of Industrial Twisted Pair (ITP) networks

cable designation

J-02YSCY 2x2x0,64/1,5 PIMF F GN

electrical data

attenuation factor per length

- at 10 MHz / maximum
- at 100 MHz / maximum
- at 300 MHz / maximum

0.057 dB/m

0.18 dB/m

0.31 dB/m

impedance

- at 1 MHz ... 100 MHz
- at 100 MHz ... 300 MHz

100 Ω

100 Ω

relative symmetrical tolerance

- of the characteristic impedance at 1 MHz ... 100 MHz
- of the characteristic impedance at 100 MHz ... 300 MHz

15 %

45 %

transfer impedance per length / at 10 MHz

2 mΩ/m

loop resistance per length / maximum

124 mΩ/m

insulation resistance coefficient

5000 GΩ·m

operating voltage

- RMS value
- maximum

165 V

225 V

mechanical data

number of electrical cores

4

design of the shield

Overlapped aluminum-clad foil (for each core), sheathed in an overall braided shield of tin-plated copper wires

core diameter

- of AWG22 insulated conductor

0.64 mm

outer diameter

- of inner conductor
- of the wire insulation

0.64 mm

1.5 mm

width / of cable sheath

9.2 mm

symmetrical tolerance of width / of cable sheath

0.5 mm

thickness / of cable sheath

6 mm

symmetrical tolerance of thickness / of cable sheath

0.5 mm

material

- of the wire insulation
- of cable sheath

polyethylene (PE)

PVC

color

<ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	<p>white/blue, white/orange green</p>
bending radius	
<ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible 	<p>30 mm 45 mm</p>
tensile load / maximum	80 N
weight per length	96 kg/km
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	<p>-40 ... +70 °C -40 ... +70 °C -40 ... +70 °C -40 ... +70 °C</p>
fire behavior	flame resistant according to IEC 60332-1
chemical resistance	
<ul style="list-style-type: none"> • to mineral oil • to grease 	<p>oil resistant according to IEC 60811-2-1 (4 h / 70°C) Conditional resistance</p>
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> • halogen-free • silicon-free 	<p>No Yes</p>
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	No
UL/ETL style / 600 V Rating	No
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval • CE marking 	<p>Yes Yes</p>
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) 	<p>No No No No No No No</p>
reference code	
<ul style="list-style-type: none"> • acc. to IEC 81346-2 • according to IEC 81346-2:2019 	<p>WG WGB</p>
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	<p>http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com</p>
last modified:	10/30/2021 