

**Accessories for  
light commercial  
vehicles and  
trucks**











**Accessories**

**2010 | 2011**



**BOSCH**

**Cable connectors**  
**universally applicable**  
 (continued)

Figure	Design	Contact width mm	Contact thickness mm	For conductor cross section mm <sup>2</sup>	Colour	Material/finish*)	Qty. per pack	Part number
	<b>Multiple butt connector</b>			0.5–1.5	red	CuZn/tin-plated	25	<b>7 781 700 027</b>
				1.5–2.5	blue	CuZn/tin-plated	25	<b>8 784 485 034</b>
				4.0–6.0	yellow	CuZn/tin-plated	25	<b>7 781 700 028</b>
	<b>Wire end ferrule</b>			up to 1.0		Cu/tin-plated	100	<b>8 780 422 000</b>
				1.0–2.5		Cu/tin-plated	100	<b>7 781 700 019</b>
				4.0–6.0		CuZn/tin-plated	100	<b>7 781 700 020</b>
	<b>Spark-plug connector</b>					CuSn/bright	50	<b>8 780 499 002</b>
	<b>Cable lug</b>	M3		0.5–1.0	red	Cu/tin-plated	100	<b>8 781 353 119</b>
				1.5–2.5	blue	Cu/tin-plated	100	<b>7 781 700 032</b>
		M4		0.5–1.0	red	Cu/tin-plated	100	<b>8 781 353 121</b>
				1.5–2.5	blue	Cu/tin-plated	100	<b>8 781 353 125</b>
				4.0–6.0	yellow	Cu/tin-plated	50	<b>7 781 700 025</b>
		M5		0.5–1.0	red	Cu/tin-plated	100	<b>8 781 353 122</b>
				1.5–2.5	blue	Cu/tin-plated	100	<b>8 781 353 126</b>
				4.0–6.0	yellow	Cu/tin-plated	100	<b>8 781 353 130</b>
		M6		0.5–1.0	red	Cu/tin-plated	100	<b>7 781 700 021</b>
				1.5–2.5	blue	Cu/tin-plated	100	<b>8 781 353 127</b>
				4.0–6.0	yellow	Cu/tin-plated	50	<b>8 781 353 131</b>
		M8		0.5–1.0	red	Cu/tin-plated	100	<b>7 781 700 022</b>
				1.5–2.5	blue	Cu/tin-plated	100	<b>8 781 353 128</b>
		M10		4.0–6.0	yellow	Cu/tin-plated	50	<b>8 781 353 132</b>
1.5–2.5	blue			Cu/tin-plated	50	<b>7 781 700 023</b>		
M4		4.0–6.0	yellow	Cu/tin-plated	50	<b>8 781 353 133</b>		
		0.5–1.0	red	Cu/tin-plated	100	<b>8 781 353 007</b>		
	<b>Open cable lug</b>	M4		4.0–6.0	yellow	Cu/tin-plated	50	<b>7 781 700 026</b>
				1.5–2.5	blue	Cu/tin-plated	100	<b>8 781 353 009</b>
				4.0–6.0	yellow	Cu/tin-plated	50	<b>8 781 353 008</b>
	<b>Open cable lug</b>	M4		1.5–2.5	blue	Cu/tin-plated	100	<b>8 781 353 000</b>
				M5		1.5–2.5	blue	Cu/tin-plated
	<b>Soldered cable lug</b>	M6		up to 3.0		Cu/tin-plated	5	<b>1 901 353 011</b>
				up to 4.0		Cu/tin-plated	5	<b>1 901 353 003</b>
				up to 5.0		Cu/tin-plated	5	<b>1 901 353 004</b>
		M8		up to 5.0		Cu/tin-plated	5	<b>1 901 353 005</b>
				up to 6.0		Cu/tin-plated	5	<b>1 901 353 006</b>
				up to 8.0		Cu/tin-plated	5	<b>1 901 353 007</b>
		M10		up to 8.0		Cu/tin-plated	5	<b>1 901 353 008</b>
				up to 10.0		Cu/tin-plated	5	<b>1 901 353 009</b>
				up to 12.0		Cu/tin-plated	5	<b>1 901 353 010</b>
	<b>Claw-type cable lug</b>	M4		0.5–2.5		CuZn/bright	100	<b>8 781 354 002</b>
		M5		0.5–2.5		CuZn/bright	100	<b>8 781 354 003</b>
		M6		0.5–2.5		CuZn/bright	100	<b>8 781 354 004</b>
		M8		0.5–2.5		CuZn/bright	100	<b>8 781 354 005</b>
		M10		4.0–6.0		CuZn/bright	50	<b>8 781 354 006</b>

\*) CuSn = bronze. CuZn = brass