












# Guards

	Description	Type	Cat. No.	
 Cat. No. 800T-N13	<b>Bul. 800T Push Button Guards</b> Momentary push button guards to reduce the risk of accidental operation.	1 in. guard for non-illuminated	800T-N13	
		1/2 in. guard for non-illuminated	800T-N143	
		1-1/2 in. guard for illuminated	800T-N93	
		1-1/2 in. guard for non-illuminated with locking attachment	800T-N39	
 Cat. No. 800H-N152	<b>Bul. 800H Illuminated Push Button Guard</b> This guard provides additional protection against accidental operation of the push button unit. 1-1/2 in. (38.1 mm) guard for illumination units.		800H-N152	
 Cat. No. 800T-N226	<b>Bul. 800T 18 mm Guard</b> Provides side protection for 18 mm pilot lights.		800T-N226	
 Cat. No. 800H-N153	<b>Bul. 800H Stainless Steel Guard</b> Used on non-illuminated push buttons that have protective boots as shown on <a href="#">page 47</a> .		800H-N153	
 Cat. No. 800T-N129	<b>Bul. 800T Mushroom Push Button Guards</b> Momentary mushroom guards for standard and jumbo mushroom push buttons. Reduces the risk of accidental operation.	Standard guard	800T-N129	
		Standard guard with set screw	800T-N165	
		Jumbo guard	800T-N151	
		Jumbo guard with set screw	800T-N154	
	<b>Description</b>	<b>Operator Head Size</b>	<b>Finish</b>	<b>Cat. No.</b>
 Cat. Nos. 800T-N310 and 800T-NX1320   Cat. No. 800T-N310J	<b>Bul. 800T/H Protective Guard</b> Stainless steel protective ring (Type 4/4X/13) for 2-position push-pull operators, illuminated, or non-illuminated. Often used in E-stop applications to avoid unintentional actuation of the E-stop operator.	40 mm (standard)	—	800T-N310
			Black	800T-NX1320
		60 mm (jumbo)	—	800T-N310J
		63 mm	—	800T-N310L
 Cat. No. 800T-NGCY	<b>Bul. 800T/H Protective Guard</b> Die-cast aluminum protective guard (Type 4/4X/13) for 2-position push-pull/twist release operators, illuminated, or non-illuminated. Often used in E-stop applications to avoid unintentional actuation of the E-stop operator.	40 mm (standard)	Yellow	800T-NGCY
 Cat. No. 800T-N381	<b>Bul. 800T/H Protective Guard</b> Die-cast aluminum protective guard (Type 4/4X/13) for 800T/H trigger action E-stop operators.	45 mm (standard)	Yellow	800T-N381
 Cat. No. 800H-NTA60G	<b>Bul. 800T/H Protective Guard</b> Yellow plastic protective guard (Type 4/4X/13) for 800T/H trigger action E-stop operators.	60/63 mm	—	800H-NTA60G
 Cat. No. 800T-N339	<b>Bul. 800T/H Ramp Guard</b> For Bul. 800T/800H 2- and 3-position illuminated and non-illuminated push-pull units. Standard-size button only (40 mm).		800T-N339	