

Product data sheet

Specifications



auxiliary contact, Acti9, iOF/SD+OF, 2OC, AC/DC

A9A26929

Main

Range of product	Acti 9
Product or component type	Double OC or fault contact
Device short name	IOF/SD+OF
Signal contacts composition	2 C/O
[In] rated current	1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC 3 A: 415 V AC - 50/60 Hz 6 A: 240 V AC - 50/60 Hz
9 mm pitches	1

Complementary

Range compatibility	Acti9 iSW-NA Acti9 iC60 Acti9 iC65 Acti9 iC60 RCBO Acti9 iID Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version) Acti9 iDPN Vigi Acti 9 iC40
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Fixed
Mounting support	DIN rail
Height	90 mm
Width	9 mm
Depth	73 mm
Net weight	43 g
Colour	White
Connections - terminals	Screw clamp terminal2 cable(s) 2.5 mm ² - rigid Screw clamp terminal2 cable(s) 1.5 mm ² - flexible with ferrule Screw clamp terminal1 cable(s) 0.5...2.5 mm ² - flexible Screw clamp terminal1 cable(s) 1...4 mm ² - rigid
Wire stripping length	10 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Tightening torque	1 N.m
-------------------	-------

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	51 g
Package 1 Height	1.801 cm
Package 1 width	7.78 cm
Package 1 Length	9.285 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	681 g
Package 2 Height	9.1 cm
Package 2 width	10.2 cm
Package 2 Length	23.6 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	120
Package 3 Weight	7.43 kg
Package 3 Height	27.3 cm
Package 3 width	28.8 cm
Package 3 Length	38.6 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

18 months