



## E32-DC200E 2M

Fiber optic sensor head, diffuse, M3 cylindrical axial, R10 fiber, 2 m cable

# Specifications

<b>Sensing method</b>	Diffuse reflective
<b>Shape</b>	Threaded
<b>Size</b>	M3
<b>Application</b>	Object detection
<b>Temperature range</b>	-40-70 °C
<b>Sensing distance</b>	240 mm
<b>Cable length</b>	2 m
<b>Bending radius</b>	10 mm
<b>Free cut</b>	✓
<b>Material core</b>	Plastic
<b>Degree of protection (IP)</b>	IP67
<b>Sensing surface orientation</b>	Top-view
<b>Material sheath</b>	Polyethylene

## Related products



### E3NX-CA

High-performance color mark sensor



### E3NX-CA

High-performance color mark sensor



### E3NX-MA

Smart Fiber Amplifier Units



### E3NX-FA

High-performance digital fiber amplifier



### E3X-NA

Digital fiber amplifier with potentiometer adjustment



### E3X-HD

Easy-teach digital fiber amplifier



### E3X-SD

Single display digital fiber amplifier



### E3X-ZV and E3X-MZV

Smart Fiber Amplifier

## Downloads

CAD Library



### Fiber Optic Sensors Group Catalogue

EN PDF 7.54 MB

