



E32-ET15YR-1 2M

Fiber optic sensor head, through-beam, square, side-view, long hole mounting, R1 flexible fiber, 2 m cable

Specifications

Sensing method	Through-beam
Shape	Square
Product Width (unpacked)	9 mm
Product Depth (unpacked)	4 mm
Product Height (unpacked)	13 mm
Application	Object detection
Features	Flexible fiber
Temperature range	-40-70 °C
Sensing distance	1800 mm
Cable length	2 m
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP67
Sensing surface orientation	Side-view
Material sheath	PVC

Related products



E3NX-CA

High-performance color mark sensor



E3NX-CA

High-performance color mark sensor



E3NX-MA

Smart Fiber Amplifier Units



E3NX-FA

High-performance digital fiber amplifier



E3X-NA

Digital fiber amplifier with potentiometer adjustment



E3X-HD

Easy-teach digital fiber amplifier



E3X-SD

Single display digital fiber amplifier



E3X-ZV and E3X-MZV

Smart Fiber Amplifier

Downloads



E32-ETS14R-1 Datasheet

EN PDF 84.8 KB



Fiber Optic Sensors Group Catalogue

EN PDF 7.54 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 7 August, 2023. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU