

Valve with Central Connector - 5599-1, Non Plug-in, Size 1 (H1)

Symbol	Type	Qn (Nl/mn)	Operator	Voltage	Pilot	Non-locking
4-Pin Central M12 Connector, 24 VDC						
		5/2 Elec. spring return	1480	Single solenoid	24 VDC	Internal H1EWXBG2B9000FD External* H1EWXXG2B9000FD
		5/2 Elec. air return	1480	Single solenoid	24 VDC	Internal H11WXBG2B9000FD External* H11WXXG2B9000FD
		5/2 dual Elec.	1480	Double solenoid	24 VDC	Internal H12WXBG2B9000FD External* H12WXXG2B9000FD
		5/3 dual Elec., all ports blocked	1180	Double solenoid	24 VDC	Internal H15WXBG2B9000FD External* H15WXXG2B9000FD
		5/3 dual Elec., center exhaust	1180	Double solenoid	24 VDC	Internal H16WXBG2B9000FD External* H16WXXG2B9000FD
		5/3 dual Elec., pressure center	1180	Double solenoid	24 VDC	Internal H17WXBG2B9000FD External* H17WXXG2B9000FD

Valve with 3-Pin DIN Connector - 5599-1, Non Plug-in, Size 1 (H1)

Symbol	Type	Qn (Nl/mn)	Operator	Voltage	Pilot	Non-locking
3-Pin DIN Connector, 24 VDC						
		5/2 Elec. spring return	1480	Single solenoid	24 VDC	Internal H1EWXBBL49D External* H1EWXXBL49D
		5/2 Elec. air return	1480	Single solenoid	24 VDC	Internal H11WXBBL49D External* H11WXXBL49D
		5/2 dual Elec.	1480	Double solenoid	24 VDC	Internal H12WXBBL49D External* H12WXXBL49D
		5/3 dual Elec., all ports blocked	1180	Double solenoid	24 VDC	Internal H15WXBBL49D External* H15WXXBL49D
		5/3 dual Elec., center exhaust	1180	Double solenoid	24 VDC	Internal H16WXBBL49D External* H16WXXBL49D
		5/3 dual Elec., pressure center	1180	Double solenoid	24 VDC	Internal H17WXBBL49D External* H17WXXBL49D

* Used with H Universal Manifold, "Internal / External" defined from the H Universal Supply module (see page 53)

Most Popular