

Data sheet

Sheet No.: HPM 2.01 RevB

Date: August 2010

HD-Series

Performance Data – (Pneumatic)

Double-Acting Actuators

HD-Series

Actuator Model	Displacement Per Stroke (cu cm) ▲	Maximum Operating Pressure (MOP)* (Bar)	Maximum Allowable Working Pressure (MAWP)** (Bar)	Approximate Weight of Actuator (kg)	With M3 Add (kg)†	With M3HW Add (kg)†	With M11 Add (kg)†
HD 521	2196	14	14	36	5	11	34
HD 721	4277	10.5	14	45	5	11	43
HD 722	7980.5	5	8.5	57	5	11	—
HD 731	5276.6	14	14	74	5	11	45
HD 732	10193	10.5	14	94	5	11	—

Spring-Return Actuators

HD-Series

Actuator Model	Displacement Per Stroke (cu cm) ▲	Maximum Operating Pressure (MOP)* (Bar)	Maximum Allowable Working Pressure (MAWP)** (Bar)	Approximate Weight of Actuator (kg)	With M3 Add (kg)†	With M3HW Add (kg)†	With M11 Add (kg)†
HD 521-SR40	2196	14	14	48	2	5	29
HD 521-SR60	2196	14	14	49	2	5	29
HD 521-SR80	2196	14	14	50	2	5	29
HD 521-SR100	2196	14	14	55	2	5	29
HD 521-SR125	2196	14	14	56	2	5	29
HD 521-SR150	2196	14	14	57	2	5	29
HD 521-SR200	2196	14	14	62	2	5	29
HD 721-SR40	4277	12.5	14	68	2	5	39
HD 721-SR60	4277	13.5	14	71	2	5	39
HD 721-SR80	4277	14	14	73	2	5	39
HD 721-SR100	4277	14	14	74	2	5	39
HD 721-SR125	4277	14	14	84	2	5	39
HD 721-SR150	4277	14	14	85	2	5	39
HD 721-SR200	4277	14	14	92	2	5	39
HD 722-SR40	7981	6	8.5	98	2	5	—
HD 722-SR60	7981	8	8.5	104	2	5	—
HD 722-SR80	7981	9	10.5	107	2	5	—
HD 722-SR100	7981	10	12	113	2	5	—
HD 732-SR40	10193	11	14	125	2	5	—
HD 732-SR60	10193	12	14	132	2	5	—
HD 732-SR80	10193	13	14	143	2	5	—
HD 732-SR100	10193	14	14	148	2	5	—
HD 732-SR125	10193	14	14	160	2	5	—
HD 732-SR150	10193	14	14	166	2	5	—

Notes:

† Manual Overrides

- M3 Jackscrew
- M3HW Jackscrew and handwheel
- M11 Piston pump assembly including hydraulic cylinder
- M7 Piston pump assembly including hydraulic cylinder

▲ Maximum volume including cavity required for calculating consumption per stroke.

* **Maximum Operating Pressure (MOP)** – The pressure required to produce the maximum rated torque of the actuator.

** **Maximum Allowable Working Pressure (MAWP)** – The maximum static pressure that may be applied to a fully stroked actuator against the travel stops.

BETTIS[™]

www.Bettis.com

Copyright © Emerson Process Management. The information in this document is subject to change without notice.

Updated data sheets can be obtained from our website www.bettis.com or from your nearest Valve Automation Center.

USA: +1 281 727 5300 Europe: +31 74 256 1010 Asia-Pacific: +65 6501 4600


EMERSON[™]
Process Management