

Product characteristics

Inductive sensor	
Rectangular, plastics	
Quick disconnect	
Dual sensor	
Sensing range 4 mm; [nf] non-flush mountable	
Electrical data	
Electrical design	DC PNP/NPN
Operating voltage [V]	10...36 DC
Protection class	II
Reverse polarity protection	yes
Outputs	
Output function	2 x normally open
Voltage drop [V]	< 4
Minimum load current [mA]	4
Leakage current [mA]	2 x 0.7
Current rating [mA]	250
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	1300
Monitoring range	
Sensing range [mm]	4
Real sensing range (Sr) [mm]	4 ± 10 %
Operating distance [mm]	0...3.25
Accuracy / deviations	
Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10
Environment	
Ambient temperature [°C]	-20...80
Protection	IP 67
Tests / approvals	
EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	1229
Mechanical data	
Mounting	non-flush mountable
Housing materials	PBT; PC (polycarbonate)
Tightening torque [Nm]	0.6...1.5 (knurled nut)
Weight [kg]	0.039
Displays / operating elements	
Output status indication LED	2 x yellow



IN5224 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Electrical connection

Connection

M12 connector; gold-plated contacts

Wiring



Remarks

Pack quantity

[piece]

1

ifm efector, inc. • 1100 Atwater Drive • Malvern • PA 19355 — We reserve the right to make technical alterations without prior notice. — US — IN5224 — 15.05.2014