

# Product data sheet

Specifications



TeSys F contactor - 3P(3 NO)-  
AC-3  $\leq$  440V 185A with coil LX9  
- 24...600V AC 40/400Hz, LX4 -  
24...460V DC, LXE - 100...250V AC  
50/60Hz or 100...380V DC

LC1F185

## Main

Range	TeSys
Product name	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Resistive load Motor control
Utilisation category	AC-3 AC-4 AC-1
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	$\leq$ 690 V AC 50/60 Hz $\leq$ 460 V DC
[Ie] rated operational current	275 A (at $<40$ °C) at $\leq$ 440 V AC-1 185 A (at $<55$ °C) at $\leq$ 440 V AC-3
Motor power kW	100 kW at 415 V AC 50/60 Hz (AC-3) 100 kW at 440 V AC 50/60 Hz (AC-3) 110 kW at 500 V AC 50/60 Hz (AC-3) 90 kW at 380...400 V AC 50/60 Hz (AC-3) 55 kW at 220...240 V AC 50/60 Hz (AC-3) 110 kW at 660...690 V AC 50/60 Hz (AC-3) 33 kW at 400 V AC 50/60 Hz (AC-4)

## Complementary

[Uc] control circuit voltage	24...575 V AC 40...400 Hz with LX9 coil 24...460 V DC with LX4 coil 100...250 V AC 50/60 Hz with LXE coil 100...380 V DC with LXE coil
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	275 A (at 40 °C)
Irms rated making capacity	1850 A conforming to IEC 60947-4-1
Rated breaking capacity	1480 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	1500 A 40 °C - 10 s 920 A 40 °C - 30 s 740 A 40 °C - 1 min 500 A 40 °C - 3 min

400 A 40 °C - 10 min

<b>Associated fuse rating</b>	200 A aM at ≤ 440 V 315 A gG at ≤ 440 V
<b>Average impedance</b>	0.33 mOhm - lth 275 A 50 Hz
<b>[Ui] rated insulation voltage</b>	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
<b>Power dissipation per pole</b>	25 W AC-1 12 W AC-3
<b>Control circuit voltage limits</b>	Operational: 0.85...1.1 U <sub>c</sub> AC 40...400 Hz with LX9 coil Drop-out: 0.2...0.55 U <sub>c</sub> AC 40...400 Hz with LX9 coil Operational: 0.85...1.1 U <sub>c</sub> DC with LX4 coil Drop-out: 0.15...0.2 U <sub>c</sub> DC with LX4 coil Operational: 85...275 V AC 50/60 Hz with LXE coil Drop-out: 0...60 V AC 50/60 Hz with LXE coil Operational: 85...418 V DC with LXE coil Drop-out: 0...45 V DC with LXE coil
<b>Heat dissipation</b>	8...9.8 W 2.2...2.5 W
<b>Operating time</b>	35 ms closing for with LX9 coil 130 ms opening for with LX9 coil 30...40 ms closing for with LX4 coil 30...50 ms opening for with LX4 coil 40...80 ms closing for with LXE coil 6...54 ms opening for with LXE coil
<b>Mounting support</b>	Plate
<b>Standards</b>	IEC 60947-4-1 EN 60947-1 JIS C8201-4-1 EN 60947-4-1 IEC 60947-1
<b>Product certifications</b>	ABS LROS (Lloyds register of shipping) RINA CSA CB UL BV RMRoS DNV UKCA
<b>Connections - terminals</b>	Power circuit: bar 2 cable(s) - busbar cross section: 25 x 3 mm Power circuit: lugs-ring terminals 1 cable(s) 150 mm <sup>2</sup> Power circuit: connector 1 cable(s) 150 mm <sup>2</sup> Power circuit: bolted connection Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> Control circuit: screw clamp terminals 1.0 cable(s) 0.2...2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1.0 cable(s) 0.25...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1.0 cable(s) 0.2...2.5 mm <sup>2</sup> solid without cable end
<b>Tightening torque</b>	Power circuit: 18 N.m Control circuit: 1.2 N.m Control circuit: 0.6 N.m
<b>Mechanical durability</b>	10 Mcycles
<b>Inrush power in VA</b>	950...1180 VA, 40...400 Hz cos phi 0.9 (at 20 °C)with LX9 coil 737...902 VA (at 20 °C)with LX4 coil 280...310 VA, 50/60 Hz cos phi 0.5 (at 20 °C)with LXE coil 270...320 VA (at 20 °C)with LXE coil
<b>Hold-in power consumption in VA</b>	8.9...10.9 VA, 40...400 Hz cos phi 0.9 (at 20 °C)with LX9 coil 4.13...5.07 VA (at 20 °C)with LX4 coil 4.5...7.0 VA, 50/60 Hz cos phi 0.5 (at 20 °C)with LXE coil 2.5...4.0 VA (at 20 °C)with LXE coil
<b>Compatibility code</b>	LC1F

## Environment

<b>IP degree of protection</b>	IP2x front face with shrouds conforming to IEC 60529 IP2x front face with shrouds conforming to VDE 0106
<b>Protective treatment</b>	TH

<b>Ambient air temperature for operation</b>	-5...55 °C
<b>Ambient air temperature for storage</b>	-60...80 °C
<b>Permissible ambient air temperature around the device</b>	-40...70 °C
<b>Mechanical robustness</b>	Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 5 Gn, 5...300 Hz Shocks contactor open: 7 Gn for 1/2 sine wave (11 ms) Shocks contactor closed: 15 Gn for 1/2 sine wave (11 ms)
<b>Height</b>	174 mm
<b>Width</b>	168.5 mm
<b>Depth</b>	181 mm
<b>Net weight</b>	5.45 kg
<b>Colour</b>	-

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	4.379 kg
<b>Package 1 Height</b>	24 cm
<b>Package 1 width</b>	27 cm
<b>Package 1 Length</b>	25 cm
<b>Unit Type of Package 2</b>	P06
<b>Number of Units in Package 2</b>	12
<b>Package 2 Weight</b>	61.108 kg
<b>Package 2 Height</b>	77 cm
<b>Package 2 width</b>	60 cm
<b>Package 2 Length</b>	80 cm

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>PVC free</b>	Yes
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

# Contractual warranty

Warranty

18 months