

Product datasheet

Specifications



M.PL.3-4V.FIXED NS-INS250 TOG.



LVS03420

Main

Range	PrismaSeT
Range Of Product	PrismaSeT P
Product Or Component Type	Mounting plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	PrismaSeT PrismaSeT P cubicle
Installation Description	Cubicle - width 650 mm depth 400 mm
Installed Device	EasyPact: fixed CVS100...160 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS250 without earth leakage protection - control: toggle - vertical installation ComPact: fixed INS250 - control: direct front rotary handle - vertical installation ComPact: fixed INV250 - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS100...160 with earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS250 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation
Poles Description	1 x 3P: fixed INS250 vertical installation 1 x 4P: fixed INS250 vertical installation 1 x 3P: fixed INV250 vertical installation 1 x 4P: fixed INV250 vertical installation 4 x 3P: fixed CVS100...160 vertical installation 3 x 4P: fixed CVS100...160 vertical installation 4 x 3P: fixed CVS250 vertical installation 3 x 4P: fixed CVS250 vertical installation 4 x 3P: fixed NSX100...160 vertical installation 3 x 4P: fixed NSX100...160 vertical installation 4 x 3P: fixed NSX250 vertical installation 3 x 4P: fixed NSX250 vertical installation 3 x 3P: fixed INS250 vertical installation 2 x 4P: fixed INS250 vertical installation 3 x 3P: fixed INV250 vertical installation 2 x 4P: fixed INV250 vertical installation

Number Of Vertical Modules [50 Mm]	<p>9 module(s): CVS100...160 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>9 module(s): CVS250 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>7 module(s): INS250, Linergy FC in 650 mm Widecubicle</p> <p>9 module(s): INS250, direct in 650 mm Widecubicle</p> <p>7 module(s): INV250, Linergy FC in 650 mm Widecubicle</p> <p>9 module(s): INV250, direct in 650 mm Widecubicle</p> <p>6 module(s): NSX100...160 without earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>8 module(s): NSX100...160 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>7 module(s): NSX250 without earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>9 module(s): NSX250 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>11 module(s): CVS100...160 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>11 module(s): CVS250 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>8 module(s): NSX100...160 with earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>10 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>9 module(s): NSX250 with earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>11 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle</p>
---	---

Standards	IEC 61439-2
------------------	-------------

Product Certifications	ASTA
-------------------------------	------

Complementary

Material	Sheet steel
-----------------	-------------

Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
-----------------------------	--

Surface Finish	Matt Textured
-----------------------	------------------

Colour	White (RAL 9003)
---------------	------------------

Width	593 mm
--------------	--------

Height	152 mm
---------------	--------

Depth	136 mm
--------------	--------

Net Weight	1.28 kg
-------------------	---------

Functional Unit	650 mm 400 mm PrismaSeT P cubicle EasyPact CVS100...160 without fixed toggle vertical 3P 4 direct 9 162.5 mm
	650 mm 400 mm PrismaSeT P cubicle EasyPact CVS100...160 without fixed toggle vertical 4P 3 direct 9 162.5 mm
	650 mm 400 mm PrismaSeT P cubicle EasyPact CVS250 without fixed toggle vertical 3P 4 direct 9 162.5 mm
	650 mm 400 mm PrismaSeT P cubicle EasyPact CVS250 without fixed toggle vertical 4P 3 direct 9 162.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 1 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 3 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 1 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 2 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 1 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 1 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 3 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INS250 fixed direct front rotary handle vertical 4P 2 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 1 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 3 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 1 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 2 Linergy FC 7 112.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 1 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 1 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 3 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 2 direct 9 212.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 3P 4 Linergy FC 6 62.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 4P 3 Linergy FC 6 62.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 3P 4 direct 8 162.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 4P 3 direct 8 162.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle vertical 3P 4 Linergy FC 7 62.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle vertical 3P 4 direct 11 162.5 mm
	650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle vertical 4P 3 direct 11 162.5 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	15.1 cm
Package 1 Length	58.8 cm
Package 1 Weight	1.53 kg
Unit Type Of Package 2	CAR
Number Of Units In Package 2	5
Package 2 Height	17.0 cm
Package 2 Width	33.5 cm
Package 2 Length	61.5 cm

Package 2 Weight	8.2 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	80
Package 3 Height	80.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	142.5 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

✓ Pvc Free

✓ Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)
