


# Product datasheet

Specifications



## PLAIN FRONT PLATE W600/ W650 4M



LVS03804

### Main

Range	PrismaSeT
Range Of Product	PrismaSeT G PrismaSeT P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle PrismaSeT PrismaSeT Pack 160 enclosure
Type Of Front Plate	Plain
Installed Device	TeSys: fixed TeSys U - horizontal installation Altistart: ATS01N103/106FT Phaseo: LV/LV transformer Enerlin'X: FDM128
Poles Description	9 x 3P: modular rail support: TeSys U horizontal installation

### Complementary

Enclosure/Cubicle Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Number Of Vertical Modules [50 Mm]	4
Standards	IEC 61439-1 IEC 61439-2
Product Certifications	ASTA
Material	Steel
Surface Finish	Matt Textured
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	200 mm
Width	500 mm
Net Weight	0.86 kg
Quantity Per Set	Set of 1

<b>Functional Unit</b>	600 mm PrismaSeT G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4
	600 mm PrismaSeT G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4
	650 mm 400 mm PrismaSeT P cubicle TeSys TeSys U fixed horizontal 3P 9 direct 4
	600 mm PrismaSeT G floor-standing enclosure Altistart ATS01N103/106FT 19 4
	600 mm PrismaSeT G wall-mounted enclosure Altistart ATS01N103/106FT 19 4
	650 mm 400 mm PrismaSeT P cubicle Altistart ATS01N103/106FT 19 4
	600 mm PrismaSeT G floor-standing enclosure Phaseo LV/LV transformer 4
	600 mm PrismaSeT G wall-mounted enclosure Phaseo LV/LV transformer 4
	650 mm 400 mm PrismaSeT P cubicle Phaseo LV/LV transformer 4
	650 mm 400 mm PrismaSeT P cubicle Enerlin'X FDM128 4 4
	555 mm Pack 160 Pack enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4
	555 mm Pack 160 Pack enclosure Altistart ATS01N103/106FT 19 4

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	3.0 cm
<b>Package 1 Width</b>	21.0 cm
<b>Package 1 Length</b>	51.0 cm
<b>Package 1 Weight</b>	862.0 g
<b>Unit Type Of Package 2</b>	BB1
<b>Number Of Units In Package 2</b>	10
<b>Package 2 Height</b>	16.5 cm
<b>Package 2 Width</b>	22.5 cm
<b>Package 2 Length</b>	52.5 cm
<b>Package 2 Weight</b>	8.812 kg
<b>Unit Type Of Package 3</b>	P12
<b>Number Of Units In Package 3</b>	360
<b>Package 3 Height</b>	100.0 cm
<b>Package 3 Width</b>	80.0 cm
<b>Package 3 Length</b>	120.0 cm
<b>Package 3 Weight</b>	329.0 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more >](#)



Transparency [RoHS/REACH](#)

## Well-being performance

✓ Reach Free Of Svhc

---

✓ Toxic Heavy Metal Free

---

✓ Mercury Free

---

✓ Rohs Exemption Information [Yes](#)

---

✓ Pvc Free

---

✓ Halogen Free Plastic Parts Product

---

## Certifications & Standards

### Reach Regulation

[REACH Declaration](#)

---

### Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

---

### China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

---

### Environmental Disclosure

[Product Environmental Profile](#)

---