


# Product datasheet

Specifications



## PLAIN FRONT PLATE W600/ W650 6M

LVS03806

### Main

|                                    |  |
|------------------------------------|--|
| Range                              | PrismaSeT  |
| Range Of Product                   | PrismaSeT G<br>PrismaSeT P   |
| Product Or Component Type          | Front plate  |
| Accessory / Separate Part Category | Installation accessory   |
| Range Compatibility                | PrismaSeT PrismaSeT G enclosure<br>PrismaSeT PrismaSeT P cubicle<br>PrismaSeT PrismaSeT Pack 160 enclosure   |
| Type Of Front Plate                | Plain  |
| Installed Device                   | Power meters: kilowatt-hour meters - vertical installation connection<br>Altistart: ATSO1N   |
| Poles Description                  | 3 x 2P: mounting plate support: kilowatt-hour meters vertical installation<br>2 x 4P: mounting plate support: kilowatt-hour meters vertical installation |

### Complementary

|                                    |  |
|------------------------------------|--|
| Enclosure/Cubicle Description      | Floor-standing enclosure - width 600 mm<br>Wall-mounted enclosure - width 600 mm<br>Cubicle - width 650 mm depth 400 mm<br>Pack enclosure - width 555 mm |
| Number Of Vertical Modules [50 Mm] | 6  |
| Standards                          | IEC 61439-2<br>IEC 61439-1   |
| Product Certifications             | ASTA   |
| Material                           | Steel  |
| Surface Finish                     | Textured<br>Matt   |
| Protective Treatment               | Electrophoresis treatment and hot-polymerised polyester epoxy powder   |
| Colour                             | White (RAL 9003)   |
| Height                             | 300 mm   |
| Width                              | 500 mm   |
| Net Weight                         | 1.22 kg  |
| Quantity Per Set                   | Set of 1   |

|                        |   |
|------------------------|---|
| <b>Functional Unit</b> | 600 mm PrismaSeT G floor-standing enclosure power meters kilowatt-hour meters vertical 2P 3 6<br>600 mm PrismaSeT G wall-mounted enclosure power meters kilowatt-hour meters vertical 2P 3 6<br>600 mm PrismaSeT G floor-standing enclosure connection 2 6<br>600 mm PrismaSeT G wall-mounted enclosure connection 2 6<br>650 mm 400 mm PrismaSeT P cubicle connection 2 6<br>600 mm PrismaSeT G floor-standing enclosure power meters kilowatt-hour meters vertical 4P 2 6<br>600 mm PrismaSeT G wall-mounted enclosure power meters kilowatt-hour meters vertical 4P 2 6<br>650 mm 400 mm PrismaSeT P cubicle power meters kilowatt-hour meters vertical 2P 3 6<br>650 mm 400 mm PrismaSeT P cubicle power meters kilowatt-hour meters vertical 4P 2 6<br>600 mm PrismaSeT G floor-standing enclosure Altistart ATS01N 9 6<br>600 mm PrismaSeT G wall-mounted enclosure Altistart ATS01N 9 6<br>600 mm PrismaSeT G floor-standing enclosure Altistart ATS01N 2 6<br>600 mm PrismaSeT G wall-mounted enclosure Altistart ATS01N 2 6<br>650 mm 400 mm PrismaSeT P cubicle Altistart ATS01N 9 6<br>650 mm 400 mm PrismaSeT P cubicle Altistart ATS01N 2 6<br>555 mm Pack 160 Pack enclosure power meters kilowatt-hour meters vertical 2P 3 6<br>555 mm Pack 160 Pack enclosure Altistart ATS01N 9 6 |
|------------------------|---|

## Packing Units

|                                     |           |
|-------------------------------------|-----------|
| <b>Unit Type Of Package 1</b>       | PCE       |
| <b>Number Of Units In Package 1</b> | 1         |
| <b>Package 1 Height</b>             | 3.0 cm    |
| <b>Package 1 Width</b>              | 31.0 cm   |
| <b>Package 1 Length</b>             | 51.0 cm   |
| <b>Package 1 Weight</b>             | 1.235 kg  |
| <b>Unit Type Of Package 2</b>       | BB1       |
| <b>Number Of Units In Package 2</b> | 10        |
| <b>Package 2 Height</b>             | 16.5 cm   |
| <b>Package 2 Width</b>              | 32.5 cm   |
| <b>Package 2 Length</b>             | 52.0 cm   |
| <b>Package 2 Weight</b>             | 12.656 kg |
| <b>Unit Type Of Package 3</b>       | P12       |
| <b>Number Of Units In Package 3</b> | 180       |
| <b>Package 3 Height</b>             | 78.0 cm   |
| <b>Package 3 Width</b>              | 80.0 cm   |
| <b>Package 3 Length</b>             | 120.0 cm  |
| <b>Package 3 Weight</b>             | 239.5 kg  |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

---

✓ Toxic Heavy Metal Free

---

✓ Mercury Free

---

✓ Rohs Exemption Information Yes

---

✓ Pvc Free

---

✓ Halogen Free Plastic Parts Product

---

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

---

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

---

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

---

**Environmental Disclosure**

[Product Environmental Profile](#)

---