


Product datasheet

Specifications



LINERGY FC DISTRIBUTION BLOCK FOR COMPACT NSX250 4P TOGGLE/FIXED+CONNECTION

LVS04404

Price* : 8,382.20 ZAR

Main

Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FC
Accessory / separate part category	Connection accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle
Provided equipment	Prefabricated flexible connection to Linergy busbars

Complementary

Installation description	Cubicle - width 650 mm
Number of devices	3 (4P)
Poles description	4P
Installed device	ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: fixed INS250 - control: direct front rotary handle - vertical installation ComPact: fixed INV250 - control: direct front rotary handle - vertical installation
Mounting support	Mounting plate
Installation direction	Horizontal
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	675 A at 40 °C
[Ue] rated operational voltage	690 V
[Ipk] rated peak withstand current	50 kA
I ² t on activation	25000000 A ² .s
Permissible current	675 A at 40 °C 615 A at 60 °C 570 A at 70 °C
Connections - terminals	Supply: flexible bars (phase / neutral) , 32 x 5 mm Outgoer: plug in (phase / neutral) , 3 outgoing

* Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Standards	IEC 61439-1 IEC 61439-2
Product certifications	KEMA ASEFA
Quantity per set	Set of 1
Length	440 mm
Height	132 mm
Depth	235 mm
Net weight	8 kg
Colour	Black


Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.4 cm
Package 1 Width	24.5 cm
Package 1 Length	46.0 cm
Package 1 Weight	6.575 kg
Unit Type of Package 2	P12
Number of Units in Package 2	35
Package 2 Height	89.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	241.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Dimensions



- All dimensions are approximate and are in mm.
- Also see technical documentation.

Recommended replacement(s)