Product datasheet

Specification





LINERGY LGYE PROFILE 800A FOR A VERTICAL INSTALLATION LENGTH 1670MM



LVS04503

Main

Range	Linergy
Range Of Product	Linergy
Product Or Component Type	Profile busbar
Product Name	Linergy LGY
Range Compatibility	PrismaSeT PrismaSeT P enclosure
Busbar Description	Linergy
Quantity Per Set	Set of 1

Complementary

Installation Direction	Vertical, operating position: rear Vertical, operating position: lateral
Installation Description	Cubicle - width 650 mm Cubicle - width 650 + 150 mm
[Ui] Rated Insulation Voltage	1000 V
[Uimp] Rated Impulse Withstand Voltage	12 kV (degree of pollution: 3)
[le] Rated Operational Current	800 A
[lcw] Rated Short-Time Withstand Current	25 kA (1 s) for 3 supports (rear position) 30 kA (1 s) for 3 supports (lateral position) 30 kA (1 s) for 4 supports (rear position)
Permissible Current	840 A at 35 °C: <= IP31 760 A at 35 °C: > IP31
Busbar Cross Section	32.5 x 42.5 mm
Length	1670 mm
Net Weight	1.64 kg
Colour	Natural
Type Of Busbar Connection	Single t-slot
Connection Pitch	Free connection position

Environment

Standards	IEC 61439-2 IEC 61439-1
Product Certifications	ΔΥΔ

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.750 cm
Package 1 Width	4.750 cm
Package 1 Length	177.000 cm
Package 1 Weight	1.584 kg
Unit Type Of Package 2	BB1
Number Of Units In Package 2	4
Package 2 Height	7.500 cm
Package 2 Width	9.500 cm
Package 2 Length	177.000 cm
Package 2 Weight	6.345 kg
Unit Type Of Package 3	PAL
Number Of Units In Package 3	80
Package 3 Height	29.000 cm
Package 3 Width	120.000 cm
Package 3 Length	200.000 cm
Package 3 Weight	148.500 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc
	Toxic Heavy Metal Free
	Mercury Free
	Rohs Exemption Information Yes
	Pvc Free
	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins