



Roof plate, PrismaSeT P, for enclosure W 300mm D 400mm, **IP30**

LVS08433

Main

Range	PrismaSeT
Range Of Product	PrismaSeT P
Product Or Component Type	Roof
Range Compatibility	PrismaSeT PrismaSeT P enclosure
Device Application	Low voltage electrical distribution
Enclosure Type	Metal enclosure
Installation Description	Cubicle duct - width 300 mm, depth 400 mm
Standards	IEC 61439-1 for enclosure IEC 61439-2 for enclosure
Product Certifications	ASTA

Complementary

Material	Treated sheet steel
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Textured Matt
Colour	White (RAL 9003)
Special Colour Options	Yes
Width	300 mm
Depth	400 mm
Net Weight	1.36 kg
Quantity Per Set	Set of 1

Environment

Ip Degree Of Protection	IP30 for enclosure
Ik Degree Of Protection	IK08

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	32.5 cm
Package 1 Length	42.5 cm

Package 1 Weight	1.41 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	120
Package 2 Height	93.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	180.5 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc
	Toxic Heavy Metal Free
	Mercury Free
	Rohs Exemption Information Yes
Ø	Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile