Product datasheet

Specifications



Roof plate, PrismaSeT P, for enclosure W 800mm D 400mm, IP30

LVS08438

Main

Range	PrismaSeT
Range Of Product	PrismaSeT P
Product Or Component Type	Roof
Range Compatibility	PrismaSeT PrismaSeT P enclosure
Device Application	Low voltage electrical distribution
Enclosure Type	Metal enclosure
Installation Description	Cubicle - width 800 mm, depth 400 mm Cubicle - width 650 + 150 mm
Standards	IEC 61439-1 for enclosure IEC 61439-2 for enclosure
Product Certifications	ASTA

Complementary

Material	Treated sheet steel
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Textured Matt
Colour	White (RAL 9003)
Special Colour Options	Yes
Width	800 mm
Depth	400 mm
Net Weight	3.54 kg
Quantity Per Set	Set of 1

Environment

Ip Degree Of Protection	IP30 for enclosure
Ik Degree Of Protection	IK08

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	42.0 cm

Package 1 Length	83.0 cm
Package 1 Weight	3.52 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	60
Package 2 Height	83.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	223.0 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
EU RoHS Declaration
China RoHS declaration
Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile