



M2R 660-11-K-Y

- Rubber enclosure
- soldering terminals and spade terminals
- Metal coating

Data

Ordering data

Product type description	M2R 660-11-K-Y
Article number (order number)	101055396
EAN (European Article Number)	4030661005331
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

General data

Standards	EN IEC 60947-5-1
Gross weight	108 g

General data - Features

Number of normally closed (NC)	1
Number of normally open (NO)	1

Mechanical data

Mechanical life, minimum	3,000,000 Operations
Actuating speed, minimum	1 mm/min

Mechanical data - Connection technique

Terminal designations	H05VV-F
Wire cross-section	0.75 mm ²

Ambient conditions

Degree of protection	IP65
Ambient temperature	-30 ... +80 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	250 VAC
Rated impulse withstand voltage U_{imp}	4 kV

Electrical data

Thermal test current	4 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	1 A
Switching principle	Snap action with self-cleaning contact
Switching frequency	30,000 /h
Material of the contacts, electrical	Gold-plated silver (AgNi 15 + Au 0,3µm)

Pictures

Product picture (catalogue individual photo)




ID: KM660F06

| 323.3 kB | .jpg | 226.836 x 351.719 mm - 643 x 997 px - 72 dpi

| 50.7 kB | .png | 74.083 x 114.653 mm - 210 x 325 px - 72 dpi

Dimensional drawing basic component



ID: Km660g02

| 123.5 kB | .jpg | 352.778 x 236.714 mm - 1000 x 671 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 01/06/2023, 13:30