

Mini Stacker 1KC-2.2LB 1INCH-25.4MM							
Identification	1.2	Manufacturer's type designation		MES150	MES150A	MES150B	MES150/801
	1.4			hand			
	1.5	Load Capacity / rated load	Q(Kg)	150			
Weights	2.1	Service weight	kg	58	56	54	60
Wheels, Chassis	3.1	Tyres:solid rubber,superelastic, pneumatic,polyurethane		Polyurethane			
	3.2	Tyre size,front	mm	75×32			
	3.3	Tyre size,rear	mm	100×32			
Basic Dimensions	3.5	Wheels,number		4			
	4.2	Lowered mast height	h₁(mm)	1958			
	4.4	Lift height	h _s (mm)	1420	1435	1440	1400
	4.15	Lowered height	h ₁₃ (mm)	130	115	110	65
	4.19	Overall length	I₁(mm)	880	865	920	920
	4.21	Overall width	b,(mm)	520	500	500	801
	4.22	Fork dimensions	I(mm)	460	445	500	500
	4.25	Width over forks	b₅(mm)	520	400(⊕ 40×2)	Φ60	650
Performance Data	5.2	Lift speed, laden/unladen	mm/s	67/82			
	5.3	Lowering speed,laden/unladen	mm/s	96/89			
E-Motor	6.1	Lift motor rating	W	90			
	6.2	Battery acc.to BS,no		NO			
	6.3	Battery voltage, nominal capacity	V/AH	2X12/7			

