







FIRE AND SECURITY SOLUTIONS FOR SMALL AND MEDIUM-SIZED BUSINESSES

Cost-effective fire, surveillance, access, and intrusion detection solutions



Smart Credentials

OmniClass 2.0 compatible smart credentials

The cost-effective OmniClass smart credentials are ideal for the majority of access control applications and are delivered with a programmed card number printed on the surface. As smart cards can also store data for other applications, such as cashless vending and storing biometric data, the 16kb OmniClass credentials become suitable for campuses and other facilities where a single card is issued. Off the shelf pre-programmed Mifare Classic and Mifare DESFire EV1 credentials are also compatible with the OmniClass 2.0 reader range. Custom programmed Mifare Classic and DESFire EV1 is optional, available for both credentials and readers.

	PART NUMBER	FORM FACTOR	SUITABLE FOR PRINTING	COLOUR	MEMORY SIZE	PROGRAMMED NUMBER	NUMBER OF BITS IN CARD FORMAT	CARD NUMBERS VISIBLE	COMPATIBLE READERS
	OKP0N34	PVC Credit card size card		White with Honeywell logo	OmniClass 2k2; 2kb, for 2 partitions	According to your requirements on site code and card number range	34 bit	Card number inkjet printed on the credential for easy identification and enrolment	OmniClass 2.0 Smart Card readers OmniClass 2.0 Multi Technology readers
	OKP0N26						26 bit		
	OKP2N34	PVC Credit card size card		White with Honeywell logo	OmniClass 16k16; 16kb, for 16 partitions	According to your requirements on site code and card number range	34 bit	Card number inkjet printed on the credential for easy identification and enrolment	OmniClass 2.0 Smart Card readers OmniClass 2.0 Multi Technology readers BioClass reader
	OKP2N26						26 bit		
	PXKEYH16K16	Key fob		Purple and Black	OmniClass 16k16; 16kb, for 16 partitions	According to your requirements on site code and card number range	34 bit	Card number inkjet printed on the credential for easy identification and enrolment	OmniClass 2.0 Smart Card readers OmniClass 2.0 Multi Technology readers BioClass reader
	PXKEYH16K1626						26 bit		

Mifare Classic and Mifare DESFire EV1 credentials for OmniClass 2.0

	PART NUMBER	FORM FACTOR	SUITABLE FOR PRINTING	COLOUR	MEMORY SIZE	PROGRAMMED NUMBER	NUMBER OF BITS IN CARD FORMAT	CARD NUMBERS VISIBLE	COMPATIBLE READERS
	PVCHMF1KSE	PVC Credit card size card		White	Mifare Classic 1kb, for 15 sectors	According to your requirements on site code and card number range; programmed in one of the sectors	34 bit	Card number inkjet printed on the credential for easy identification and enrolment	OmniClass 2.0 smart card readers OmniClass 2.0 Multi Technology readers
	PVCHMF1KSE26						26 bit		
	PVCHDF8KSE				DESFire EV1 8kb, multiple applications		34 bit		
	PVCHDF8KSE26						26 bit		