

PLC-BSP- 24DC/21 - Relay base



2967219

<https://www.phoenixcontact.com/pc/products/2967219>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



6.2 mm PLC basic terminal block with spring-cage connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 changeover contact, input voltage 24 V DC

Commercial Data

Item number	2967219
Packing unit	10 pc
Minimum order quantity	1 pc
Sales Key	08
Product Key	CK6221
GTIN	4017918164294
Weight per Piece (including packing)	26.31 g
Weight per Piece (excluding packing)	24.64 g
Customs tariff number	85366990
Country of origin	DE

PLC-BSP- 24DC/21 - Relay base



2967219

<https://www.phoenixcontact.com/pc/products/2967219>

Conductor cross section AWG	26 ... 14
-----------------------------	-----------

Signaling

Status display	LED
----------------	-----

Dimensions

Width	6.2 mm
Height	80 mm
Depth	94 mm

Material specifications

Flammability rating according to UL 94	V0 (Housing)
--	--------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any