



Safety gate system with guard locking, with radius actuator, interlocking principle spring force, contacts 2 n/o, 2 n/c, supply voltage 24 V AC/DC.

## Technical details

### General data

Approval:	CCC, CE, BG, cCSAus, EAC (Eurasian)
unit type:	Unit

### Technical data

#### Electrical data

Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	AC/DC
Power consumption AC:	4.4
Power consumption DC:	4.4

#### Relay outputs

Utilisation cat. AC/DC1 stand.:	EN 60947-4-1
Voltage AC1 safety cont.:	240
Max. current AC1 safety cont.:	2.5
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	230
Max. current AC15 safety cont.:	2.5

#### Environmental data

Ambient temperature:	-25 - 70 °C
Protection type, housing:	IP67

#### Mechanical data









Holding force:	1500
Connection terminal:	Federkraftklemme
Terminal style:	fest
Height dimension:	184 mm
Width dimension:	42.5 mm
Depth dimension:	51 mm
Net weight:	335 g
Gross weight:	513 g
<b>Environment</b>	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE klassifikation (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27272603
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002593

## Optional accessories



380706

PDP67 cable M12-5sm, 10m

	380707	PDP67 cable M12-5sm, 20m
	380705	PDP67 cable M12-5sm, 3m
	380708	PDP67 cable M12-5sm, 30m
	540312	PSEN screw M5x20 10pcs
	570101	PSEN me1AS
	773600	PDP67 F 8DI ION
	570102	PSEN me1AR
	570793	PSEN cable 200m-8x0.25mm <sup>2</sup>