


Redundancy module - QUINT-DIODE/40 - 2938963

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Redundancy module QUINT-DIODE/40



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 929534
GTIN	4017918929534
Weight per Piece (excluding packing)	680.000 g
Custom tariff number	85049090
Country of origin	China

Technical data

Dimensions

Width	62 mm
Height	84 mm
Depth	102 mm
Installation distance right/left	5 mm / 5 mm
Installation distance top/bottom	50 mm / 50 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 70 °C (> 60 °C derating, # -25 ... 60°C)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, non-condensing)

Redundancy module - QUINT-DIODE/40 - 2938963

Technical data

Ambient conditions

Degree of pollution	2
---------------------	---

Input data

Nominal input voltage	24 V DC
Nominal input voltage range	24 V DC
Input voltage range	0 V DC ... 30 V DC
Nominal input current	2x 20 A
	1x 40 A
Maximum input current	2x 19 A (6 mm ² at 40°C)
	1x 39 A (6 mm ² at 40°C)
	2x 16 A (6 mm ² at 60°C)
	1x 32 A (6 mm ² at 60°C)
	2x 27 A (10 mm ² at 40°C)
	1x 54 A (10 mm ² at 40°C)
	2x 21 A (10 mm ² at 60°C)
	1x 43 A (10 mm ² at 60°C)
	2x 30 A (16 mm ² at 40 °C)
	1x 60 A (16 mm ² at 40 °C)
	2x 24 A (16 mm ² at 60°C)
	1x 48 A (16 mm ² at 60°C)

Output data

Nominal output voltage	24 V DC
Nominal output current (I _N)	40 A
Connection in series	No
Power loss nominal load max.	20 W

General

Net weight	0.7 kg
Efficiency	> 97 %
MTBF (IEC 61709, SN 29500)	28571428 h (40 °C)
Insulation voltage input / PE	1 kV
Insulation voltage output / PE	1 kV
Degree of protection	IP20
Protection class	II (in closed control cabinet)
Mounting position	horizontal and vertical DIN rail NS 35, EN 60715
Assembly instructions	alignable: horizontal 20 mm, vertical 50 mm

Connection data, input

Redundancy module - QUINT-DIODE/40 - 2938963

Technical data

Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	10 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	6
Stripping length	10 mm
Screw thread	M4

Connection data, output

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	10 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	6
Stripping length	10 mm
Screw thread	M4

Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Noise emission	EN 55011
Noise immunity	EN 61000-6-2:2005
Standards/specifications	EN 60079-0
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
Shipbuilding approval	DNV GL (EMC A), ABS
UL approvals	UL/C-UL listed UL 508
	UL/C-UL Recognized UL 60950-1
	UL/C-UL Listed UL 1604 Class I, Division 2, Groups A, B, C, D
ATEX	# II 3G Ex nA IIC T4 Gc
	KEMA 03 ATEX 1197X

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Redundancy module - QUINT-DIODE/40 - 2938963

Drawings

Block diagram

