

## 7800 SERIES and R7140 Flame Signal Amplifiers



Dynamic Self Check



Standard

Solid state plug-in amplifiers that respond to flame detector inputs to indicate the presence of flame when used with 7800 SERIES relay modules.

- Flame failure response time of 0.8 or 3.0 seconds.
- Flame signal strength ranges from 0.0 to 5.0 Vdc.
- Plug into 7800 relay module through printed circuit board edge connector keyed for proper orientation.
- Flame signal test jacks to measure amplifier flame signal voltage.
- Color-coded labels identify flame detection type. Dynamic Self-Check Amplifier test the detectors and all electronic components in the flame detection system 7800 SERIES relay module locks out on safety shutdown with flame detection system failure.
- Compatible with existing Honeywell flame detectors (order separately).

**Use With Primary Safety Control:** RM7824  
R7824C1002 only

**Use With Primary Safety Control:** 7800 SERIES Relay Modules  
All other Amplifiers

**Approvals:**

**Canadian Standards Association:** Certified: File No. LR95329-3

**Factory Mutual:** Approved: Report No. J.I.1V9A0.AF

**Underwriters Laboratories Inc.** Listed: File No. MP268, Guide No. MCCZ

Product Number	Flame Failure Response Time (sec)	Self Checking	Use With Flame Sensor	Comments
R7824C1002	3.0 sec	Dynamic Self-Check	C7024E, F Flame Detector	Color: Green
R7847A1025	0.8 sec or 1.0 sec	None (standard)	Gas: Rectifying Flame Rods C7004, C7005, C7007, C7008, C7009, Q179	Color: Green
R7847A1033	2.0 sec or 3.0 sec	None (standard)	Gas: Rectifying Flame Rods C7004, C7005, C7007, C7008, C7009, Q179 Gas, oil, coal: Ultraviolet Flame Sensor C7012A,C	Color: Green
R7847A1074	0.8 sec or 1.0 sec	None (standard)	Gas: Rectifying Flame Rods C7004,5,7,8, or 9, Q179 for impedance matching for leadwire runs > 50' or Ultraviolet Flame Sensor C7012A,C	Color: Green
R7847A1082	2.0 sec or 3.0 sec	None (standard)	Gas: Rectifying Flame Rods C7004,5,7,8, or 9, Q179 for impedance matching for leadwire runs > 50' or Ultraviolet Flame Sensor C7012A,C	Color: Green
R7847B1023	0.8 sec or 1.0 sec	Ampli-Check	Gas: Rectifying Flame Rods C7004, C7005, C7007, C7008, C7009, Q179	Color: Green
R7847B1031	2.0 sec or 3.0 sec	Ampli-Check	Gas: Rectifying Flame Rods C7004, C7005, C7007, C7008, C7009, Q179 Gas, oil, coal: Ultraviolet Flame Sensor C7012A, C	Color: Green
R7847B1064	0.8 sec or 1.0 sec	Ampli-Check	Gas: Rectifying Flame Rods C7004,5,7,8, or 9, Q179 for impedance matching for leadwire runs > 50' or Ultraviolet Flame Sensor C7012A,C	Color: Green
R7847B1072	2.0 sec or 3.0 sec	Ampli-Check	Gas: Rectifying Flame Rods C7004,5,7,8, or 9, Q179 for impedance matching for leadwire runs > 50' or Ultraviolet Flame Sensor C7012A,C	Color: Green
R7847C1005	2.0 sec or 3.0 sec	Dynamic Self-Check	Gas, oil, coal: Ultraviolet Flame Sensor C7012E, F	Color: Green
R7848A1008	2.0 sec or 3.0 sec	None (standard)	Gas, oil, coal: Infrared (lead sulfide) C7015	Color: Red
R7848B1006	2.0 sec or 3.0 sec	Ampli-Check	Gas, oil, coal: Infrared (lead sulfide) C7015	Color: Red
R7849A1015	0.8 sec or 1.0 sec	None (standard)	Gas, Oil: Minipeeper C7027A, C7035A, C7044	Color: Purple
R7849A1023	2.0 sec or 3.0 sec	None (standard)	Gas, Oil: Minipeeper C7027A, C7035A, C7044	Color: Purple
R7849B1013	0.8 sec or 1.0 sec	Ampli-Check	Gas, Oil: Minipeeper C7027A, C7035A, C7044	Color: Purple
R7849B1021	2.0 sec or 3.0 sec	Ampli-Check	Gas, Oil: Minipeeper C7027A, C7035A, C7044	Color: Purple
R7851B1000	2.0 sec or 3.0 sec	Ampli-Check	Gas, Oil, Coal: Optical (UV, Visible Light) C7927, C7962	Color: White
R7851B1018	0.8 sec or 1.0 sec	Ampli-Check	Gas, Oil, Coal: Optical (UV, Visible Light) C7927, C7962	Color: White
R7851C1008	2.0 sec or 3.0 sec	Dynamic Self-Check	Gas, oil, coal: optical (UV only) C7961E,F	Color: White
R7852A1001	2.0 sec or 3.0 sec	None (standard)	Gas, oil, coal: Infrared (lead sulfide) C7915	Color: Red/White
R7852B1009	2.0 sec or 3.0 sec	Ampli-Check	Gas, oil, coal: Infrared (lead sulfide) C7915	Color: Red/White
R7861A1026	2.0 sec or 3.0 sec	Dynamic Self-Check	Gas, oil, coal: Ultraviolet Flame Sensor C7061	Color: Purple
R7861A1034	0.8 sec or 1.0 sec	Dynamic Self-Check	Gas, oil, coal: Ultraviolet Flame Sensor C7061	Color: Purple
R7886A1001	2.0 sec or 3.0 sec	Dynamic Self-Check	Gas, oil, coal: Adjustable Sensitivity Ultraviolet Flame Sensor C7076	Color: Blue