

Eaton TIA32M40

Catalog Number: TIA32M40

Fuse-link, LV, 32 A, AC 660 V, DC 460 V, BS88/A2, 22 x 86 mm, gM, BS, 32M40

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage British standard fuse	TIA32M40 UPC 051712392938
EAN	Product Length/Depth
5027590514248	86 mm
Product Height	Product Width
23 mm	23 mm
Product Weight	Warranty
57.7 g	Not Applicable
Compliances	
Contact Manufacturer	

Electrical rating

Amperage Rating

40 A

Breaking capacity

80 kA

Interrupt rating

80 kAIC

Rated switching capacity

80 kA

Voltage rating

660 V

Voltage type

AC/DC

Physical details

Color

None

Fuse type

TIA

General information

Class

Class gM

Connection

73 mm fixing centre

Construction size

A2

Fitted with:

Offset bolted tags

Fuse indicator

None

Fuse shape

Offset bolted tags

Fuse size

BS88/A2

Insulated metal gripping lugs (IMGL)

No

Utilization category

gM (motor protection)

Resources

Catalogs

[TIA32M40–Eaton Bussmann series low voltage British standard fuse](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA Redspot fuse-links](#)

[CE Redspot fuse-links](#)

Specifications and datasheets

[Eaton Specification Sheet - TIA32M40](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)