



Fuse-link, low voltage, 50 A, AC 660 V, DC 460 V, 80 kA, BS88/A3, 22 x 86 mm, gL/gG, BS

Part no. **50A 690V AC / 460V DC gG INDUSTRIAL FUSE**
 Catalog No. **TIS50**

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|---------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 50 |
| Rated voltage | | | AC 660 V DC 460 V |
| Construction size | | | BS88/A3 |
| Size | | | 22 x 86 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 80 |
| usable for size/applications | | | general industrial applications |
| Standard/Approval | | | BS |
| Shape | | | offset bolted tags |
| Standards/Regulations | | | BS88-2 IEC 60269-2 |
| Optional accessories | | | fuse-holder RS63 |

Technical data ETIM 8.0

| | | | |
|--|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) | | | |
| Fuse construction type according to IEC 60269 | | | |
| Type of current | | | |
| Rated voltage AC | | V | 660 |
| Rated voltage DC | | V | 460 |
| Rated current | | A | 50 |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Breaking capacity | | kA | 80 |
| Colour code | | | |
| Type of fuse status indicator | | | None |
| Power loss at rated current | | W | |
| Mounting holes | | | |
| Centre-to-centre distance of connections | | mm | |