

## DIGITAL BATTERY TESTER WITH PRINTER

### 890 K

PROMO



- Measures the state of charge, the capacity and efficiency of the batteries from 6 to 12V, also with "Start & Stop" system
- Checks the alternator efficiency and the starting system from 12V to 24V
- It allows you to test batteries: EFB, flat AGM, SPIRAL AGM, VRLA / GEL, standard Liquid
- LCD screen
- Thermal printer (no ink required)
- 6 languages selectable
- Cables length: 2 m
- Supplied in a plastic case with shock-resistant shell and 2 rolls of paper
- Spare cables: code BAT.TEST-C

Battery diagnosis (V)	6-12
Display	LCD
Battery capacity (Ah)	SAE (CCA): 40÷3000 A, EN: 40÷2830 A, DIN: 25÷1685 A, IEC: 30÷1985 A
Start and Stop Battery capacity (Ah)	SAE (CCA): 40÷2000 A, EN: 40÷2100 A, DIN: 25÷1300 A, IEC: 30÷1500 A
Battery type (supplied)	4 x AA
Charge system (V)	12-24

### Family details

Code	LxPxH mm	Quantity for packaging
U08901000	305x90x205	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000



Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo  
da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000