Product data sheet

Specifications



Limit switch head, Limit switches XC Standard, ZC2J, without lever spring return left and right actuation

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

1

ZC2JE01

Main	
Range of product	OsiSense XC
Series name	Special format
Product or component type	Limit switch head
Device short name	ZC2J
Head type	Rotary head
Product compatibility	XC2J
Associated lever	ZC2JY13 ZC2JY12 ZC2JY11 ZC2JY91 ZC2JY51 ZC2JY81 ZC2JY31
Associated body	ZC2JC2 ZC2JC28 ZC2JC18 ZC2JD2 ZC2JC1 ZC2JD1
Movement of operating head	Rotary
Type of operator	Without operating lever spring return
Type of approach	Lateral approach, 2 directions
Complementary	
Switch actuation	From left and right CW and CCW
Positive opening	Without
Net weight	0.21 kg
Head material	Metal
Environment	
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Standard environment

Life Is On Schneider

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.800 cm
Package 1 Width	9.500 cm
Package 1 Length	4.800 cm
Package 1 Weight	220.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	14
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.300 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty

18 months

Recommended replacement(s)